

# PRODUCT DATASHEET LED TUBE T5 HF L13 SHORT VALUE 517 mm 7W 840

LED TUBE T5 HF SHORT VALUE | LED tubes for electronic high frequency control gear (ECG), shatterproof



## Areas of application

- General illumination within ambient temperatures from -20...+45  $^{\circ}\text{C}$
- Public buildings
- Kitchens
- Under-cabinet lighting

#### Product benefits

- No bending thanks to glass technology
- Quick, simple and safe replacement without rewiring
- Also suitable for operation at low temperatures
- Please follow all safety advices

#### Product features

- Retrofit replacement of existing T5 lamps on HF ballast installations
- Lamp tube made of glass with splinter protection
- High color consistency: ≤ 5 sdcm
- Lifetime up to 30,000 h
- Low flicker according to EU 2019-2020 (SVM  $\leq 0.4$  / PstLM  $\leq 1)$
- Type of protection: IP20
- Compatible with many common electronic control gears (see also compatibility list)



mm 7W 840



## **TECHNICAL DATA**


## Electrical data

Nominal wattage	7 W
Nominal voltage	3055 V
Operating mode	ECG <sup>1)</sup>
Nominal current	215 mA
Type of current	AC
Inrush current	21 A
Operating frequency	2575 kHz
Mains frequency	2575 kHz
Total harmonic distortion	120 %
Power factor $\lambda$	0.59

<sup>1)</sup> Check ECG compatibility at ledvance.com/compatibility

## Photometrical data

Luminous flux	850 lm
Luminous efficacy	121 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4



EPREL data spectral diagram PROF LEDr 4000K

# Light technical data

Beam angle	190 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight



Overall length	530.00 mm
Length with base excl. base pins/connection	517.00 mm
Diameter	18.50 mm
Product weight	68.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+45 °C ¹)
Maximum temperature at tc test point	65 °C
Performance temp. acc. to IEC 62717	40 °C <sup>2)</sup>

<sup>1)</sup> Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

## Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

## Additional product data

Base (standard designation)	G5
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted

# Capabilities

<sup>2)</sup>  $\ensuremath{\mathsf{Tp}}$  rated.  $\ensuremath{\mathsf{Tp}}$  point coincides with  $\ensuremath{\mathsf{Tc}}$  point - marked on device

Dimmable	No	
Certificates & Standards		
Energy efficiency class	E 1)	

Energy efficiency class	E 1)
Energy consumption	7.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA / EAC
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

## Country-specific categorizations

Temperature range at storage

Order reference

LOGISTICAL DATA			

LEDTUBE T5HF L1

-20...+80 °C

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G5
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Networked standby power for CLS	0 W
Claim of equivalent power	No
Length	530.00 mm
Height	18.50 mm
Width	18.50 mm
Chromaticity coordinate x	0,382
Chromaticity coordinate y	0,38
R9 Colour rendering index	1

Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0,86
LED light source replaces a fluorescent light source	No
EPREL ID	1392491
Model number	AC46404,AC46404

## Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- Not suitable for emergency lighting.

## DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	LED TUBE T5 HF SHORT LEDV	
PDF	User instruction / safety instructions		
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity	LED TUBE T5 HF SHORT	
PDF	Declarations of conformity UKCA	LED TUBE T5 HF SHORT	
PDF	ECG compatibility list	Ballast compatibility LEDVANCE LED TUBE T5 HF_T8 HF_T8 UNIVERSAL 2025	
	Photometric and lighting design files Document name		
	IES file (IES)	LEDTUBE T5 HF L13 SHORT V 517 7W 840 LEDV	
	LDT file (Eulumdat)	LEDTUBE T5 HF L13 SHORT V 517 7W 840 LEDV	
	UGR file (UGR table)	LEDTUBE T5 HF L13 SHORT V 517 7W 840 LEDV	
	Light distribution curve type polar	LEDTUBE T5 HF L13 SHORT V 517 7W 840 LEDV	

Photometric and lighting design files	Document name
Spectral power distribution	EPREL data spectral diagram PROF LEDr 4000K


Tender texts	Document name
Tender documents	LED TUBE T5 HF SHORT V 517 mm 7W 840-EN

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075823679	Sleeve 1	23 mm x 23 mm x 533 mm	82.00 g	0.28 dm <sup>3</sup>
4058075823686	Shipping box 25	545 mm x 121 mm x 129 mm	2172.00 g	8.51 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### ADDITIONAL CATALOG INFORMATION



### References / Links

- For current information see www.ledvance.com/ledtube

## Legal advice

- When used to replace a T5 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.