

PRODUCT DATASHEET DULUX LED S7 EM & AC MAINS VALUE 3.5W 840 G23

DULUX LED S EM & AC MAINS VALUE | LED replacement for short CFLni with 2-pin G23 base for CCG and AC mains operation



Areas of application

- General illumination within ambient temperatures from -20...+45 $^{\circ}\text{C}$
- Supermarkets and department stores
- Walkways and corridors
- Hotels, restaurants

Product benefits

- Easy installation
- Low energy consumption
- Easy relamping thanks to compact design
- Operation directly on 230 V AC mains possible

Product features

- LED replacement for conventional compact fluorescent lamps for use in CCG luminaires or on AC mains
- Lifetime up to 30,000 h
- Single-ended two-pin plug-in G23 base
- Type of protection: IP20
- Mercury-free lamps





TECHNICAL DATA

Electrical data


Nominal wattage	3.5 W
Construction wattage	3.50 W
Nominal voltage	220240 V
Operating mode	CCG, AC Mains
Claimed equiv. conventional lamp power	7 W
Nominal current	16 mA
Type of current	AC
Inrush current	11.2 A
Suitable for DC input	Yes
Input voltage DC	186260 V ¹⁾
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	53
Max. lamp number on MCB B10 A - CCG without compensation	250
Max. lamp number on MCB B10 A - CCG with compensation	14
Max. lamp number on MCB B16 A	67
Max. lamp number on MCB B16 A - CCG without compensation	355
Max. lamp number on MCB B16 A - CCG with compensation	17
Total harmonic distortion	≤ 30 %
Power factor λ	> 0.90

¹⁾ Permitted voltage range

Photometrical data

Luminous flux	400 lm
Nominal useful luminous flux 90°	400 lm
Luminous efficacy	114 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤6 sdcm

Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



EPREL data spectral diagram PROF LEDr 4000K

Light technical data

Beam angle	130 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	135.00 mm
Diameter	32.30 mm
Tube diameter	26,0 mm
Maximum diameter	33 mm
Product weight	34.00 g

Temperatures & operating conditions

Ambient temperature range	-20+45 °C ¹⁾
Maximum temperature at tc test point	78 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	G23
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted

Capabilities

Dimmable	No

Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	4.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG0

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Order reference	DULUX LED S7 EM
LOGISTICAL DATA	

Temperature range at storage	-20+80 °C
------------------------------	-----------

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G23
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No

Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	No
Length	135.00 mm
Height	32.30 mm
Width	32.30 mm
Chromaticity coordinate x	0.381
Chromaticity coordinate y	0.379
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	0.90
LED light source replaces a fluorescent light source	No
EPREL ID	1404755,2206833,2324450
Model number	AC46407,AC71129,AC81521

Safety advice

- Suitable for tandem operation.
- The operating temperature range of DULUX LED is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Do not touch the lamp with bare fingers.
- Must not be used if outer bulb is defective.
- Lamp not suitable for emergency operation.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DULUX LED S EM V
PDF	Extended installation guide	Installation instructions LED TUBE T8, T5 und DULUX LED 2024 10 EN
POF	Extended installation guide	LEDVANCE Luminaire conversion checklist
POF	Legal information	Informationstext 18 Abs 4 ElektroG

	Documents and certificates	Document name
PDF	Declarations of conformity	DULUX LED
PDF	Declarations of conformity	LEDTUBE
PDF	Declarations of conformity UKCA	DULUX LED
PDF	Declarations of conformity UKCA	LEDTUBE
	Photometric and lighting design files	Document name
	IES file (IES)	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	IES file (IES)	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	LDT file (Eulumdat)	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	LDT file (Eulumdat)	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	UGR file (UGR table)	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	UGR file (UGR table)	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	Light distribution curve type cone	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	Light distribution curve type cone	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	Light distribution curve type polar	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	Light distribution curve type polar	DULUX LED S7 EM V 3.5W 840 G23 LEDV
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 4000K
	Tender texts Doo	cument name
	Tender documents DU	LUX LED S EM AC MAINS VALUE 3.5W 840 G23-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075822955	Folding box	24 mm x 35 mm x 141 mm	50.00 g	0.12 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075822962	Shipping box 10	128 mm x 79 mm x 152 mm	578.00 g	1.54 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.