

PRODUCT DATASHEET LED TUBE T8 EM FOOD 600 mm 5.2W 833

LED TUBE T8 EM FOOD | LED tubes for electromagnetic control gear (CCG) and AC mains, shatterproof, for food presentation



Areas of application

- Food presentation in e.g. butchers, bakeries, supermarkets or meat processors
- Suitable for ambient temperatures of -20 to +50 $^{\circ}\text{C}$

Product benefits

- Food looks fresh and appetizing without unduly "beautifying" it
- Quick, simple and safe replacement of fluorescent lamps without rewiring the CCG
- Energy savings of up to 74 % (compared to T8 fluorescent lamp)
- Shatter protection thanks to special PET coating
- Support the implementation of the HACCP concepts from production through to presentation
- No bending thanks to glass tube
- Also suitable for operation at low temperatures

Product features

- Specially tailored spectral distribution (comparable to T8 FL NATURA 76)
- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG luminaires or on AC mains
- Lamp tube made of glass with splinter protection e.g. for food industry applications
- ENEC 10 VDE mark
- Type of protection: IP20



- Mercury-free and RoHS compliant

TECHNICAL DATA


Electrical data

Nominal wattage	5.2 W
Construction wattage	5.20 W
Nominal voltage	220240 V
Operating mode	CCG, AC Mains
Nominal current	24 mA
Type of current	AC
Inrush current	2.92 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz ¹⁾
Max. lamp number on MCB B10 A	205
Max. lamp number on MCB B10 A - CCG without compensation	87
Max. lamp number on MCB B10 A - CCG with compensation	30
Max. lamp number on MCB B16 A	257
Max. lamp number on MCB B16 A - CCG without compensation	109
Max. lamp number on MCB B16 A - CCG with compensation	35
Total harmonic distortion	< 20 %
Power factor λ	> 0.90

¹⁾ DC 0Hz

Photometrical data

Luminous flux	500 lm
Luminous efficacy	96 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	NATURA
Color temperature	3300 K
Color rendering index Ra	80
Light color	833
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80



Spectral graph LEDTUBE T8 FOOD

Light technical data

Beam angle	190 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	603.00 mm
Length with base excl. base pins/connection	600.00 mm
Diameter	26.70 mm
Product weight	100.00 g

Temperatures & operating conditions

Ambient temperature range	-20+50 °C ¹⁾
Maximum temperature at tc test point	60 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	60000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	G13	
Mercury content	0.0 mg	
Mercury-free	Yes	
Capabilities		
Dimmable	No	
Certificates & Standards		
Energy consumption	6.00 kWh/1000h	
Type of protection	IP20	
Standards	CE / UKCA / VDE / ENEC / EAC	
Photobiological safety group acc. to EN62778	RG0	
Country-specific categorizations		
Order reference	LEDTUBE T8 EM F	
LOGISTICAL DATA		
Temperature range at storage -20+80 °C		
Francisco de la Miser de de descripción de la constitución de la const		
Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	LED	
Non-directional or directional	NDLS	
Mains or non-mains	MLS	
Light source cap-type (or other electric interface)	G13	
Connected light source (CLS)	No	
Color-tuneable light source	No	
Envelope	No	
High luminance light source	No	
Anti-glare shield	No	
Standby power	0 W	
Claim of equivalent power	No	
Length	603.00 mm	
Height	26.70 mm	
Width	26.70 mm	
Chromaticity coordinate x	0.3684	
Chromaticity coordinate y	0.2816	

70

R9 Colour rendering index

Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No

EQUIPMENT / ACCESSORIES

- Suitable for operation with low-loss and conventional control gears

Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- Not suitable for emergency lighting.
- Disconnect mains before installation.

DOWNLOAD DATA

DOWNLOAD I	DATA		
	Documents and certificates	Document name	
PDF	User instruction / safety instructions	LEDTUBE T8 EM FOOD P	
PDF	Extended installation guide	Notes on the operation of LEDVANCE LED tubes in compensated luminaires	
PDF	Extended installation guide	LEDVANCE Luminaire conversion checklist	
PDF	On-Pack-Info	ELR - exempt lamps	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity	LEDTUBE T8 EM FOOD P	
PDF	Declarations of conformity UKCA	LEDTUBE T8 EM FOOD P	
	Photometric and lighting design files	Document name	
	IES file (IES)	LEDTUBE T8 EM FOOD P 600 5.2W 833 LEDV	
	LDT file (Eulumdat)	LEDTUBE T8 EM FOOD P 600 5.2W 833 LEDV	

Light distribution curve type polar LEDTUBE T8 EM FOOD P 600 5.2W 833 LEDV Spectral power distribution Spectral graph LEDTUBE T8 FOOD	Photometric and lighting design files	s Document name
Spectral power distribution Spectral graph LEDTUBE T8 FOOD	Light distribution curve type polar	LEDTUBE T8 EM FOOD P 600 5.2W 833 LEDV
	Spectral power distribution	Spectral graph LEDTUBE T8 FOOD
Tender texts Document name	Tender texts	Document name

LED TUBE T8 EM FOOD P 600 mm 5.2W 833-EN



Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854044793	Sleeve 1	695 mm x 29 mm x 29 mm	118.00 g	0.58 dm ³
4099854044809	Shipping box 10	725 mm x 180 mm x 95 mm	1502.00 g	12.40 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/ledtube

Tender documents

Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

833