

# PRODUCT DATASHEET LED VALUE HIGHBAY 150 W 4000 K

LED VALUE HIGHBAY GEN 2 | High-bay luminaires



#### Areas of application

- Warehouses
- Factory
- Logistics halls
- Public areas
- Airports
- Indoor sports facilities

#### **Product benefits**

- Energy savings thanks to high system efficacy: up to 120 lm/W
- Tough and heavy duty thanks to the aluminum die-cast housing tempered glass
- Low maintenance costs thanks to long lifetime

#### Product features

- Driver on board technology platform
- $-\,$  Available with wattage: 60 W, 83 W, 125 W, 150 W and 200 W
- $-\,$  Standard CCT: 6500 K and 4000 K
- Input voltage: 220...240 V
- Color rendering index R<sub>a</sub>: ≥ 80
- Power factor: > 0.9
- Luminous efficacy: 120 lm/W
- Type of protection: IP65
- Impact resistance: IK06
- Safety compliance certificates: CB, EMC, RoHS 2.0

## **TECHNICAL DATA**

## Electrical data

Nominal wattage	150.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.90
Protection class	I

# Photometrical data

Luminous flux	18000 lm
Luminous efficacy	120 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	80
Standard deviation of color matching	≤5 sdcm
Beam angle	105 °

# Dimensions & Weight

Diameter	260.00 mm
Height	50.00 mm
Product weight	1500.00 g



#### Materials & Colors

Product color	Black/Gray
Housing color	Black/Gray
Body material	Aluminum
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-30+50 °C
Type of protection	IP65
Dimmable	No

Mounting type	Surface/Suspended
Application environment	Indoor
With light source	Yes
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	LDVAL HB 150W 840 G2

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075739031	Shipping box	75 mm x 295 mm x 305 mm	1844.00 g	6.75 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.