

PRODUCT DATASHEET LED Classic Globe 95 60 Filament Energy efficiency class A S 3.8W 840 Clear E27

LED CLASSIC GLOBE ENERGY EFFICIENCY A S | LED lamps, classic ball shape, ENERGY EFFICIENCY CLASS A



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lamps with innovative LED "filament" technology
- Low energy consumption
- Design, dimensions, luminous flux comparable to a halogen lamp
- Instant 100 % light, no warm-up time
- Low flickering

Product features

- LED lamps for line voltage
- Luminous efficacy: up to 210 lm/W
- Beam angle: up to 300°
- Very long lifetime of up to 50,000 h
- Very high number of switching cycles 500,000






TECHNICAL DATA

Electrical data

| Nominal wattage | 3.8 W |
|--|----------|
| Construction wattage | 3.80 W |
| Nominal voltage | 220240 V |
| Operating mode | AC Mains |
| Claimed equiv. conventional lamp power | 60 W |
| Nominal current | 35 mA |
| Type of current | AC |
| Inrush current | 3.52 A |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp number on MCB B10 A | 136 |
| Max. lamp number on MCB B16 A | 172 |
| Total harmonic distortion | 135 % |
| Power factor λ | ≥ 0.40 |

Photometrical data

| Luminous flux | 806 lm |
|---|------------|
| Luminous efficacy | 212 lm/W |
| Lumen main.fact.at end of nom.life time | 0.96 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | 80 |
| Light color | 840 |
| Standard deviation of color matching | ≤6 sdcm |
| Flickering metric (Pst LM) | ≤1.0 |
| Stroboscope effect metric (SVM) | ≤0.4 |



Spectral graph Globe95 4000K

Light technical data

| Beam angle | 300 ° |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight

| 0 | |
|------------------|-----------|
| Overall length | 135.00 mm |
| Diameter | 95.00 mm |
| Maximum diameter | 95 mm |
| Product weight | 55.00 g |

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|--------------------------------------|-----------|
| Maximum temperature at tc test point | 80 °C |

Lifespan

| Lifespan L70/B50 at 25 °C | 50000 h |
|--|---------|
| Number of switching cycles | 500000 |
| Lumen maintenance at end of service lifetime | 0.96 |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------|--|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Clear |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| Dimmable | No |
|----------|----|
| | |

Certificates & Standards

| Energy efficiency class | A 1) |
|-------------------------|------|
|-------------------------|------|

| Energy consumption | 4.00 kWh/1000h |
|--|-----------------|
| Type of protection | IP20 |
| Standards | CE / EAC / UKCA |
| Photobiological safety group acc. to EN62778 | RG0 |

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

| 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency) | | | |
|--|----------------------------------|--|--|
| Country-specific categorizations | Country-specific categorizations | | |
| Order reference | LEDG9560EELA 3. | | |
| LOGISTICAL DATA | | | |
| Temperature range at storage | -20+80 °C | | |
| Energy labelling regulation data acc EU 2019/2015 | | | |
| Lighting technology used | LED | | |
| Non-directional or directional | NDLS | | |
| Mains or non-mains | MLS | | |
| Light source cap-type (or other electric interface) | E27 | | |
| Connected light source (CLS) | No | | |
| Color-tuneable light source | No | | |
| Envelope | No | | |
| High luminance light source | No | | |
| Anti-glare shield | No | | |
| Correlated colour temperature type | SINGLE_VALUE | | |
| Standby power | o W | | |
| Claim of equivalent power | Yes | | |
| | | | |

135.00 mm 95.00 mm

95.00 mm

1857086,2185082,2505683

0.380

0.380

Length

Height Width

EPREL ID

Chromaticity coordinate x

Chromaticity coordinate y

| Model number | AC57903,AC70024,AC92524 |
|--------------|-------------------------|
|--------------|-------------------------|

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|---------------------------------|---------------|
| PDF | Declarations of conformity | LED Lamp |
| PDF | Declarations of conformity | LED lamps |
| PDF | Declarations of conformity UKCA | LED lamp |
| PDF | Declarations of conformity UKCA | LED lamps |

| Photometric and lighting design files | Document name |
|---------------------------------------|------------------------------|
| Spectral power distribution | Spectral graph Globe95 4000K |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854246616 | Folding box 1 | 110 mm x 110 mm x 158 mm | 111.00 g | 1.91 dm³ |
| 4099854246623 | Shipping box 10 | 564 mm x 231 mm x 175 mm | 1355.00 g | 22.80 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.