

# PRODUCT DATASHEET CONNECTED SENSOR REMOTE CONTROL

LEDVANCE CONNECTED SENSOR REMOTE | Connected Sensor Remote for LEDVANCE Connected Sensor HB and LB



#### **Product benefits**

- LEDVANCE Connected sensor remote control for easy installation
- 3 years guarantee

## Product features

- Compatible with LEDVANCE Connected Sensor HB and LB (Gen 2)
- Battery included (Lithium, 3 V)




# TECHNICAL DATA

# Electrical data

Type of current	DC
Mains frequency	5060 Hz
Light technical data	
Beam angle	15 °

# Dimensions & Weight



Product weight	60.00 g	
Additional product data		
Mercury content	0.0 mg	
Mercury-free	Yes	
Capabilities		
Dimmable	No	
Certificates & Standards		
Type of protection	IP20	
Standards	CE	
Country-specific categorizations		
Order reference	CONNECTED SENSO	
Energy labelling regulation data acc EU 20	019/2015	
Length	58.0 mm	

Height	8.00 mm
Width	94.00 mm

## Safety advice

- All electrical connections must be made by a qualified person.
- Disconnect mains before installation.

### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	User instruction / safety instructions	Connected Sensor Remote

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075374034	Folding box 1	16 mm x 71 mm x 136 mm	24.00 g	0.15 dm <sup>3</sup>
4058075374041	Shipping box 10	143 mm x 78 mm x 172 mm	277.00 g	1.92 dm <sup>3</sup>
4058075396357	Shipping box 60	486 mm x 156 mm x 192 mm	1830.00 g	14.56 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For Guarantee see www.ledvance.com/guarantee

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.