

## PRODUCT DATASHEET

### Bathroom Wall 455mm E14 Chrome

Bathroom Wall Luminaire IP44 E14 | Luminaire with socketed base and IP44



#### Areas of application

- Indoor applications
- Bathrooms (IP44)

#### Product benefits

- Socketed luminaire, the lamps can be replaced

#### Product features

- Type of protection: IP44
- The cover is made of high quality glass



TECHNICAL DATA

Electrical data

|                  |               |
|------------------|---------------|
| Nominal voltage  | 220...240 V   |
| Mains frequency  | 50...60 Hz    |
| Protection class | I             |
| Operating mode   | Mains voltage |

Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 86.00 mm  |
| Width          | 72.00 mm  |
| Height         | 455.00 mm |
| Product weight | 1442.00 g |

BATH CLASSIC  
CYLINDERW45CMIP44E14

Materials & Colors

|                                            |        |
|--------------------------------------------|--------|
| Product color                              | Chrome |
| Housing color                              | Chrome |
| Body material                              | Steel  |
| Cover material                             | Glass  |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content                            | 0.0 mg |

Application & Mounting

|                              |                        |
|------------------------------|------------------------|
| Ambient temperature range    | -20...+40 °C           |
| Temperature range at storage | -20...+80 °C           |
| Type of connection           | Screw terminal, 3-Pole |
| Type of protection           | IP44                   |
| Dimmable                     | No                     |
| Mounting type                | Surface                |
| Application environment      | Indoor                 |
| With light source            | No                     |

|                          |     |
|--------------------------|-----|
| Replaceable light source | No  |
| Holder designation       | E14 |

### Certificates & Standards

|                                                      |           |
|------------------------------------------------------|-----------|
| Standards                                            | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |
| Ball shot safe                                       | No        |

### Additional product data

|                       |                                    |
|-----------------------|------------------------------------|
| Product remark        | Maximum bulb wattage: 3 x 12 W LED |
| Number of illuminants | 3                                  |

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### DOWNLOAD DATA

| Documents and certificates                                                         |                                        | Document name                     |
|------------------------------------------------------------------------------------|----------------------------------------|-----------------------------------|
|  | User instruction / safety instructions | BATHROOM CLASSIC CYLINDER         |
|  | Legal information                      | Safety insert G11220428           |
|  | Declarations of conformity             | CE Declaration Bathroom Classic   |
|  | Declarations of conformity UKCA        | UKCA Declaration Bathroom Classic |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854444395 | Folding box<br>1             | 90 mm x 180 mm x 475 mm              | 1755.00 g    | 7.70 dm <sup>3</sup>  |
| 4099854444401 | Shipping box<br>4            | 380 mm x 200 mm x 505 mm             | 7020.00 g    | 38.38 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.