

# PRODUCT DATASHEET LED Spot Pear 3 x 4.3W 2700K GU10

LED Spot Pear White | Ceiling mounted luminaires with adjustable GU10 spotlights



#### Areas of application

- Indoor applications

#### Product benefits

- Osram lamp included

#### Product features

- GU10 lamp included
- Housing material: Plastic and Metal
- Adjustable head



# TECHNICAL DATA

# Electrical data


Nominal wattage	12.90 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	101.000 mA
Inrush current time T <sub>h50</sub>	500 μs
Max. number of luminaires per miniature circuit breaker B16	17
Max. number of luminaires per miniature circuit breaker C10	17
Max. number of luminaires per miniature circuit breaker C16	28
Power factor $\lambda$	> 0.5
Protection class	I
Operating mode	Mains voltage

# Photometrical data

Luminous flux	630 lm
Total luminous flux of contained light sources	1050 lm
Luminous efficacy	48 lm/W
Color temperature	2700 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Photobiological safety group acc. to EN62778	RG1
Beam angle	36 °
UGR	< 25

# Dimensions & Weight

Length	444.00 mm
Width	60.00 mm
Height	131.00 mm
Product weight	720.00 g



LED SPOT PEAR 430MM 3X4.3W 827 GU10

## Materials & Colors

Product color	White
Housing color	White
Body material	Plastic METAL
Glow Wire Test according to IEC 60695-2-12	650 °C

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Screw terminal, 3-Pole
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
With light source	Yes
Replaceable light source	No
Holder designation	GU10

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

# Additional product data

Product remark	Maximum bulb wattage: 5 W LED
Number of illuminants	3

#### **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### **DOWNLOAD DATA**

	Documents and certificates Document name		
User instruction / safety instructions LED		LED SPOT PEAR	
PDF	Legal information	Safety insert G11219578	
PDF	Declarations of conformity	CE Declaration Spot Pear	
PDF	Declarations of conformity UKCA		

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854473807	Folding box 1	80 mm x 130 mm x 480 mm	993.00 g	4.99 dm <sup>3</sup>
4099854473814	Shipping box 6	280 mm x 258 mm x 510 mm	5960.00 g	36.84 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.