

PRODUCT DATASHEET Orbis Milan 305 mm 2XE27 WD

ORBIS MILAN | Socketed ceiling luminaires with metal ring



Areas of application

- Indoor applications

- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Replaceable LED lamp
- Elegant design

Product features

- Decorative domestic lighting
- Ceiling luminaire with socket
- Glass and metal material



TECHNICAL DATA

Electrical data

| Nominal voltage | 220240 V |
|------------------|---------------|
| Mains frequency | 5060 Hz |
| Protection class | 1 |
| Operating mode | Mains voltage |

Dimensions & Weight

| Diameter | 305.00 mm |
|----------------|-----------|
| Height | 100.00 mm |
| Product weight | 1050.00 g |



Materials & Colors

| Product color | Wood decor |
|--|------------|
| Housing color | Wood decor |
| Body material | Steel |
| Cover material | Glass |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|------------------------------|-----------------------------|
| Temperature range at storage | -20+80 °C |
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Surface |
| Application environment | Indoor |
| With light source | No |

| Replaceable light source | No |
|--|-----------|
| Certificates & Standards | |
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |

Safety advice

- All electrical connections must be made by a qualified person.

- Caution, risk of electric shock.

 Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|--|--------------------------|
| POF | User instruction / safety instructions | ORBIS |
| PDF | Legal information | Legal Insert |
| PDF | Declarations of conformity | ORBIS MADRID PARIS MILAN |
| PDF | Declarations of conformity UKCA | ORBIS MADRID PARIS MILAN |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075829169 | Folding box 1 | 175 mm x 300 mm x 300 mm | 1409.00 g | 15.75 dm ³ |
| 4058075829176 | Shipping box 4 | 620 mm x 314 mm x 380 mm | 6404.00 g | 73.98 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.