

PRODUCT DATASHEET

LN INV D 1500 P 52W 940 DAVR WT

LINEAR INDIVILED DIRECT 1500 DALI | Surface mounted luminaire for single or light line office application with CRI90 and DALI-2 IoT technology, 1500 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Homogenous light distribution and reduced glare ($UGR \leq 19$) thanks to IndiviLED® optics
- High performance with CRI90 and up to 135 lm/W
- IoT-ready luminaire with DALI-2 driver, suitable for VIVARES and other Light Management Systems
- Symmetric light distribution for various application areas
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Suitable for battery emergency installations acc. to EN 60598-2-22
- Multiple mounting options thanks to different accessories

Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color



- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)
- Pendant mounting with suspension kit (to be ordered separately)
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Lifetime (L80/B10): 70,000 h (at 25 °C)
- Multi lumen function: programmable DALI-2 driver


TECHNICAL DATA

Electrical data


Nominal wattage	52 W / 48 W / 44 W / 39 W
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	232...210...200...185 mA
Inrush current	25.2 A
Inrush current time T_{h50}	40 μ s
Max. number of luminaires per miniature circuit breaker B16	29
Max. number of luminaires per miniature circuit breaker C10	23
Max. number of luminaires per miniature circuit breaker C16	38
Power factor λ	> 0.90
Total harmonic distortion	$\leq$ 20 %
Protection class	I
Operating mode	Integrated LED driver
Dimming interface	DALI-2 / IoT

Photometrical data

Luminous flux	6400 lm / 6000 lm / 5850 lm / 5250 lm
Luminous efficacy	123 lm/W / 125 lm/W / 133 lm/W / 135 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq$ 90
Standard deviation of color matching	3 sdc _m
Low flicker	Yes
Flickering metric (Pst LM)	$\leq$ 1
Stroboscope effect metric (SVM)	$\leq$ 0.4
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	90 °
UGR	< 19
1	



LN INV D 1500 P 52W 940 DAVR WT 1050mA




LN INV D 1500 P 52W 940 DAVR WT

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
52 W	4000 K	6400 lm	123 lm/W
48 W	4000 K	6000 lm	125 lm/W
44 W	4000 K	5850 lm	133 lm/W
39 W	4000 K	5250 lm	135 lm/W

Dimensions & Weight

Length	1475.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3820.00 g



LN INV 1500 P

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9003
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	DALI2
IoT ready	Support of DALI data type PART 251, 252, 253 ¹⁾
Mounting type	Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Adjustable	No
With light source	Yes
Replaceable light source	Yes

1) Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	1050mA / 975mA / 900mA / 800 mA
ECG - Output ripple current	≤ 5 %
Recommended control gear	OSRAM type OTI DALI 50/220-240/1A4 NFC L

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00027-V01.01-EN
Replaceable light source (EPREL)	By the end consumer

Additional product data

Number of illuminants	1
Added function	EVERLOOP / VIVARES / Programmable Multi Lumen

Accessories Optional

Product image	Product name	EAN
	LN INV SUSPENSION KIT WT	4099854215537
	LN INV SUSPENSION WIRE	4099854323980

Product image	Product name	EAN
	LN INV 1500 THROUGHWIRING KIT	4099854214806
	LN INV INLINE CONNECTOR	4099854215612
	LN INV CORNER CONNECTOR WT	4099854308093
	LN INV INFILL 600 WT	4099854214882
	LN INV INFILL 1200 WT	4099854214868
	LN INV INFILL 1500 WT	4099854214844

EQUIPMENT / ACCESSORIES

- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available

Upgrade and replacement components

Components Light Source		
Product image	Product name	EAN
	LISOEV 1339x29 65 52W 940 S90U19 GY	4099854284854
Components Driver		

Product image	Product name	EAN
	OTi DALI 50/220...240/1A4 NFC L	4062172074988

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LN INV D PS
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Safety Insert G11205497
	Legal information	Legal Insert G11235610
	Legal information	LN INV D DI
	Declarations of conformity	LN INV
	Declarations of conformity UKCA	LN INV
	EU Data Act	DALI LED Driver and Luminaires
Photometric and lighting design files		Document name
	IES file (IES)	LN INV D 1500 P 52W 940 DAVR WT 1050mA
	LDT file (Eulumdat)	LN INV D 1500 P 52W 940 DAVR WT 1050mA
	ULD file (DIALux)	LN INV D 1500 P 52W 940 DAVR WT


Photometric and lighting design files		Document name
	ROLF file (RELUX)	LN INV D 1500 P 52W 940 DAVR WT
	UGR file (UGR table)	LN INV D 1500 P 52W 940 DAVR WT 1050mA
	Light distribution curve type cone	LN INV D 1500 P 52W 940 DAVR WT 1050mA
	Light distribution curve type polar	LN INV D 1500 P 52W 940 DAVR WT 1050mA
	Light distribution curve type polar	LN INV D 1500 P 52W 940 DAVR WT
CAD/BIM files		Document name
	BIM Revit 3D	Linear Indiviled G2
	CAD STEP 3D	LN INV D 1500 G2
Tender texts		Document name
	Tender documents	LINEAR INDIVILED DIRECT 1500 DALI 1500 P 52W 940 DAVR WT-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854136061	Folding box 1	1,252 mm x 167 mm x 87 mm	4520.00 g	18.19 dm ³
4099854136078	Shipping box 2	1,547 mm x 187 mm x 189 mm	10640.00 g	54.68 dm ³



The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



LINEAR Indiviled® DIRECT DALI WT	DRIVER	mA	W	lm	lm/W	°
LN INV D 1200 P 40W 930 DAVR WT	OSRAM OTI DALI HV 500-SM 1A4 NFC L	500 600 700	25 30 36	2100 2700 3200	120 120 120	NFC
LN INV D 1200 P 40W 940 DAVR WT	OSRAM OTI DALI HV 500-SM 1A4 NFC L	500 600 700	25 30 36	2100 2700 3200	120 120 120	Phosphor
LN INV D 1500 P 52W 930 DAVR WT	OSRAM OTI DALI HV 500-SM 1A4 NFC L	500 600 700	25 30 36	2100 2700 3200	120 120 120	NFC
LN INV D 1500 P 52W 940 DAVR WT	OSRAM OTI DALI HV 500-SM 1A4 NFC L	500 600 700	25 30 36	2100 2700 3200	120 120 120	Phosphor

LINEAR Indiviled® DIRECT DALI	DRIVER	mA	W	lm	lm/W	°
LN INV D 1200 P 40W 930 DAVR WT	OSRAM OTI DALI HV 500-SM 1A4 NFC L	500 600 700	25 30 36	2100 2700 3200	120 120 120	NFC
LN INV D 1200 P 40W 940 DAVR WT	OSRAM OTI DALI HV 500-SM 1A4 NFC L	500 600 700	25 30 36	2100 2700 3200	120 120 120	Phosphor
LN INV D 1500 P 52W 930 DAVR WT	OSRAM OTI DALI HV 500-SM 1A4 NFC L	500 600 700	25 30 36	2100 2700 3200	120 120 120	NFC
LN INV D 1500 P 52W 940 DAVR WT	OSRAM OTI DALI HV 500-SM 1A4 NFC L	500 600 700	25 30 36	2100 2700 3200	120 120 120	Phosphor



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.