

# PRODUCT DATASHEET Endura Classic GU10 IP65 Isidor Wall Dark Gray

ENDURA® Classic IP65 GU10 | Wall luminaires with dark grey aluminum housing, IP65 protection, glass diffuser and GU10 socket



#### Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

## Product benefits

- High flexibility in the choice of the light source thanks to GU10 socket
- Easy and quick installation

#### **Product features**

- Options with PIR motion detector and daylight sensor available
- Indirect illumination
- Die-cast aluminum housing
- Glass or PMMA diffuser
- Anthracite housing color

## **TECHNICAL DATA**

## Electrical data

| Nominal voltage  | 220240 V      |
|------------------|---------------|
| Mains frequency  | 5060 Hz       |
| Protection class | 1             |
| Operating mode   | Mains voltage |

# Dimensions & Weight

| Length         | 60.00 mm  |
|----------------|-----------|
| Width          | 88.00 mm  |
| Height         | 170.00 mm |
| Product weight | 450.00 g  |



# Materials & Colors

| Product color                              | Dark gray |
|--|-----------|
| Housing color                              | Dark gray |
| Body material                              | Aluminum  |
| Cover material                             | Glass     |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C    |

# Application & Mounting

| Ambient temperature range              | -20+40 °C                   |
|--|-----------------------------|
| Type of connection                     | Terminal, 3-Pole (L, N, PE) |
| Type of protection                     | IP65                        |
| Protection class IK (shock resistance) | IK05                        |
| Dimmable                               | No                          |
| Mounting type                          | Surface                     |
| Mounting location                      | Wall                        |
| Application environment                | Outdoor                     |
| With light source                      | No                          |
| Replaceable light source               | No                          |

| Holder designation | GU10 |
|--------------------|------|
|                    |      |

#### Certificates & Standards

| Standards  | CE / UKCA |
|--|-----------|
| Luminaire with limited surface temperature, "D sign" | No        |

## Additional product data

| Product remark        | Maximum bulb wattage: 35W (7W LED) |
|-----------------------|------------------------------------|
| Number of illuminants | 1                                  |

#### **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### DOWNLOAD DATA

|     | Documents and certificates             | Document name          |
|-----|--|------------------------|
| PDF | User instruction / safety instructions | Endura Itys            |
| PDF | Legal information                      | Legal insert I-Outdoor |
| PDF | Declarations of conformity             | Endura Classic IP65    |
| PDF | Declarations of conformity UKCA        | Endura Classic IP65    |

#### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854183003 | Folding box                  | 72 mm x 97 mm x 182 mm               | 495.00 g     | 1.27 dm <sup>3</sup> |
| 4099854183010 | Shipping box<br>4            | 220 mm x 170 mm x 215 mm             | 2187.00 g    | 8.04 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.