

PRODUCT DATASHEET

LDV BAT 600 12-20W TRI

Wattage Switch Tri Colour Batten | Linear luminaires available in TRI CCT with dual wattage switch for ultimate versatility in one fitting



Areas of application

- Reception areas and foyers
- Garages
- Corridors, stairways, entrance areas
- Entrances / Hallways
- Retail
- Hospitality

Product benefits

- Available in 4 housing sizes with TRI CCT
- Easy installation

Product features

- Beam angle: 120°
- Type of protection: IP20
- Polycarbonate housing
- Lifetime up to 50,000 h
- High luminous efficacy: up to 110 lm/W
- DALI version and self-contained emergency versions are available within the same family

TECHNICAL DATA

Electrical data

Nominal wattage	20.00 W
-----------------	---------

Photometrical data

Luminous flux	2000 lm
Luminous efficacy	100 lm/W

Dimensions & Weight

Length	600.00 mm
Width	75.00 mm
Height	73.00 mm
Product weight	880.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Dimmable	No
Mounting type	Surface
Replaceable light source	No

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075603233	Folding box 1	607 mm x 90 mm x 90 mm	995.00 g	4.92 dm³
4058075603240	Shipping box 6	645 mm x 260 mm x 180 mm	6380.00 g	30.19 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.