

PRODUCT DATASHEET

LDV BAT 1200 22-40W TRI DALI

Wattage Switch Tri Colour Batten | Linear luminaires available in TRI CCT with dual wattage switch for ultimate versatility in one fitting



Areas of application

- Reception areas and foyers
- Garages
- Corridors, stairways, entrance areas
- Entrances / Hallways
- Retail
- Hospitality

Product benefits

- Available in 4 housing sizes with TRI CCT
- Easy installation

Product features

- Beam angle: 120°
- Type of protection: IP20
- Polycarbonate housing
- Lifetime up to 50,000 h
- High luminous efficacy: up to 110 lm/W
- DALI version and self-contained emergency versions are available within the same family

TECHNICAL DATA

Electrical data

Nominal wattage	40.00 W
-----------------	---------

Photometrical data

Luminous flux	4000 lm
Luminous efficacy	100 lm/W

Dimensions & Weight

Length	1185.00 mm
Width	75.00 mm
Height	73.00 mm
Product weight	1700.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)

Application & Mounting

Dimmable	Yes
Type of dimming	DALI
Mounting type	Surface
Replaceable light source	No

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075616578	Folding box 1	1,203 mm x 80 mm x 80 mm	1900.00 g	7.70 dm³
4058075616585	Shipping box 6	1,230 mm x 260 mm x 180 mm	12200.00 g	57.56 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

