

# PRODUCT DATASHEET FL H M POWER SUPPLY V 300W

FLOODLIGHT HIGH MAST POWER SUPPLY | Floodlight High Mast power supplies



#### Areas of application

- Outdoor use (IP66)
- Suitable for high mast applications
- Lighting of large areas
- Construction areas
- Industry

## Product benefits

- Highly robust and durable
- Optimized product logistic, luminaire heads and power supplies to be ordered separately in stand-alone packaging
- 5 years guarantee

#### Product features

- Power supply for floodlight high mast luminaire heads
- Joint or separate installation with floodlight high mast power supply
- M16 cable gland for mains cable


## **TECHNICAL DATA**

## Electrical data

Nominal wattage	300.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 15 %
Protection class	I

# Dimensions & Weight

Length	317.00 mm
Width	201.00 mm
Height	61.00 mm
Product weight	1700.00 g



FL H M POWER SUPPLY V

## Materials & Colors

Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-40+50 °C
Temperature range at storage	-40+70 °C

Type of protection	IP66/IP66
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting location	Wall / Pole / Floor
With light source	No
Replaceable light source	No

# Lifespan

Number of switching cycles	100000

# Certificates & Standards

Standards	CE / LVD / EMC / ROHS / REACH / SLR / ENEC	
Luminaire with limited surface temperature, "D sign"	No	

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	Floodlight High Mast
PDF	User instruction / safety instructions	FL H M LUM V_POWER SUPPLY_PONTER HOLDER_ CUT OFF HOOD_ WIRE GUARD
PDF	Legal information	FL H M
PDF	Legal information	FL H M LUM V_POWER SUPPLY_PONTER HOLDER_ CUT OFF HOOD_ WIRE GUARD
PDF	Declarations of conformity	CE Declaration FL H M
PDF	Declarations of conformity UKCA	FL HIGH MAST
PDF	Certificates	FL H M
PDF	Certificates	FL H M LUM V
	Tender texts	Document name
	Tenuer texts	DOCUMENT NAME
	Tender documents	FLOODLIGHT HIGH MAST POWER SUPPLY 300W-EN

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854196508	Folding box 1	230 mm x 70 mm x 328 mm	1843.00 g	5.28 dm <sup>3</sup>
4099854196515	Shipping box 4	348 mm x 306 mm x 260 mm	7873.00 g	27.69 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For Guarantee see www.ledvance.com/guarantee

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.