

# PRODUCT DATASHEET

## DR DS-P- 32/220-240/750 PL FLEX 625

PANEL FLEX DRIVER | Constant current



---

### Areas of application

- Suitable for PANEL FLEX 30 W / 32 W

---

### Product benefits

- High flexibility due to adjustable output currents with a switch on the driver
- Low flickering enables high light quality as well as good visual comfort
- High efficiency and reliability
- 7 years guarantee

---

### Product features

- Available in 30 W, 32 W
- Protection class: II
- Type of protection: IP20
- Supply voltage: 220...240 V
- Operating frequency: 0/50/60 Hz
- Suitable for central battery emergency installations acc. to EN 60598-2-22


## TECHNICAL DATA

### Electrical data

|                           |              |
|---------------------------|--------------|
| Nominal wattage           | 32.00 W      |
| Nominal voltage           | 220...240 V  |
| Mains frequency           | 0/50/60 Hz   |
| Nominal current           | 700 mA       |
| Inrush current            | 11.1 A       |
| Power factor $\lambda$    | > 0.90       |
| Total harmonic distortion | < 15 %       |
| Protection class          | II           |
| Dimming interface         | Not dimmable |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 125.00 mm |
| Width          | 60.00 mm  |
| Height         | 30.00 mm  |
| Product weight | 105.00 g  |



DR DS-P PL FLEX

### Materials & Colors

|                 |         |
|-----------------|---------|
| Body material   | Plastic |
| Mercury content | 0.0 mg  |

### Application & Mounting

|                              |              |
|------------------------------|--------------|
| Ambient temperature range    | -10...+50 °C |
| Temperature range at storage | -20...+80 °C |
| Type of protection           | IP20         |
| Dimmable                     | No           |

## Control gear

|                        |          |
|------------------------|----------|
| Nominal output current | 750 mA   |
| ECG lifetime           | 100000 h |






## Certificates &amp; Standards

|           |  |
|-----------|--|
| Standards | CE / CB / ENEC / UKCA / EAC / EPD / EL |
|-----------|--|

## Additional product data

|                |                          |
|----------------|--------------------------|
| Product remark | Available from June 2024 |
|----------------|--------------------------|

## DOWNLOAD DATA

| Documents and certificates   |  | Document name                                   |
|--|--|---|
|    | User instruction / safety instructions | DR DS-P PL FLEX                                 |
|    | Legal information                      | DR DS-SENS- SF FL                               |
|   | Legal information                      | Informationstext 18 Abs 4 ElektroG              |
|  | Declarations of conformity             | Driver PL FLEX                                  |
| Tender texts   |  | Document name                                   |
|  | Tender documents                       | PANEL FLEX DRIVER 32 220 240 750 PL FLEX 625-en |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075843691 | Folding box<br>1             | 82 mm x 34 mm x 182 mm               | 154.00 g     | 0.51 dm <sup>3</sup>  |
| 4058075843837 | Shipping box<br>20           | 427 mm x 157 mm x 217 mm             | 3438.00 g    | 14.55 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

– For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

