

PRODUCT DATASHEET

FLASHLIGHT SPOTLIGHT TRANSFORM

FLASHLIGHT SPOTLIGHT TRANSFORM | Outdoor mobiles



Areas of application

- Multifunctional

Product benefits

- 4 operating modes: 1 press: bright light 300 lm, 2nd press: soft light 100 lm, 3rd press: side light, 4th press: flashing mode
- 1,5 h of running at full brightness
- 3,5 h of running at side light mode
- 6 hours to fully charge from empty-to-full
- Battery capacity: 2400 mA
- Power Bank mode

Product features

- Charging indicator
- Convenient button for switching modes
- COB LED for side light.
- Type of protection: IP64

TECHNICAL DATA

Electrical data

| | |
|--------------------------------------|---------|
| Nominal wattage | 3.00 W |
| Inrush current | 1 A |
| Inrush current time T _{h50} | 0.5 s |
| Operating mode | Battery |

Photometrical data

| | |
|---------------------------|------------|
| Luminous flux | 300 lm |
| Luminous efficacy | 100 lm/W |
| Color temperature | 6500 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | 70 |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 110.00 mm |
| Width | 110.00 mm |
| Height | 160.00 mm |
| Product weight | 560.00 g |

Materials & Colors

| | |
|-----------------|----------------------------------|
| Product color | Black |
| Housing color | Black |
| Body material | ABS I TPR (Thermoplastic rubber) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Type of connection | USB Type-C |
| Dimmable | No |
| Adjustable | No |
| With light source | Yes |
| Replaceable light source | No |

Lifespan

| | |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
|---------------------------|-----------------------|

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

| | |
|-----------------------|-------|
| Battery size [GMS] | 18650 |
| Battery charging time | 6 h |




Certificates & Standards

| | |
|----------------------------------|-----------------|
| Standards | CE / UKCA |
| Replaceable light source (EPREL) | Not replaceable |

EQUIPMENT / ACCESSORIES

– USB C cable

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|----------------------------|------------------------------------|
|  | Legal information | Informationstext 18 Abs 4 ElektroG |
|  | Legal information | FLASHL |
|  | Declarations of conformity | CE Declaration Flashlight |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854175763 | Folding box 1 | 212 mm x 117 mm x 167 mm | 637.00 g | 4.14 dm ³ |
| 4099854440113 | Shipping box 10 | 393 mm x 285 mm x 393 mm | 5920.00 g | 44.02 dm ³ |
| 4099854583964 | Shipping box 10 | 610 mm x 350 mm x 250 mm | 7423.00 g | 53.38 dm ³ |
| 4099854175770 | Shipping box 20 | 600 mm x 355 mm x 455 mm | 13881.00 g | 96.92 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.