

PRODUCT DATASHEET

FLASHLIGHT CAMPING

CAMPING LIGHT | Outdoor mobiles



Areas of application

- Multifunctional

Product benefits

- 2 operating modes: 1 press: bright light 100 lm, 2nd press: soft light 30 lm
- 3 hours of running at full brightness
- 9 built-in LEDs
- 4 hours to fully charge from empty-to-full
- Battery capacity: 1200 mAh
- Can be hanged, put on floor, worn on the head or used in hands
- Adjustable head strap included
- Durable and high quality materials

Product features

- Hinge to adjust light direction
- Strap connectors. Can be used with or without it.
- Convenient button for switching modes
- Charging port
- Type of protection: IP20

TECHNICAL DATA

Electrical data

| | |
|--------------------------------------|---------|
| Nominal wattage | 1.50 W |
| Inrush current | 390 mA |
| Inrush current time T _{h50} | 0.5 s |
| Operating mode | Battery |

Photometrical data

| | |
|---------------------------|------------|
| Luminous flux | 100 lm |
| Luminous efficacy | 67 lm/W |
| Color temperature | 6500 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | 70 |

Dimensions & Weight

| | |
|----------------|----------|
| Length | 86.00 mm |
| Width | 56.00 mm |
| Height | 75.00 mm |
| Product weight | 154.00 g |

Materials & Colors

| | |
|-----------------|----------------------------------|
| Product color | Orange |
| Housing color | Orange |
| Body material | ABS I TPR (Thermoplastic rubber) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Type of connection | USB Type-C |
| Dimmable | No |
| Adjustable | No |
| With light source | Yes |
| Replaceable light source | No |

Lifespan

| | |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
|---------------------------|-----------------------|

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

| | |
|-----------------------|-------|
| Battery size [GMS] | 18650 |
| Battery charging time | 4 h |



Certificates & Standards

| | |
|----------------------------------|-----------------|
| Standards | CE / UKCA |
| Replaceable light source (EPREL) | Not replaceable |

EQUIPMENT / ACCESSORIES

– USB C cable

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|-------------------|------------------------------------|
|  | Legal information | Informationstext 18 Abs 4 ElektroG |
|  | Legal information | FLASHL |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854175527 | Folding box 1 | 92 mm x 62 mm x 85 mm | 176.00 g | 0.48 dm ³ |
| 4099854583872 | Shipping box 6 | 290 mm x 190 mm x 175 mm | 1369.00 g | 9.64 dm ³ |
| 4099854175534 | Shipping box 48 | 387 mm x 283 mm x 335 mm | 9096.00 g | 36.69 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.