

# PRODUCT DATASHEET Damp proof Essential Extrusion 18W 600mm 840

Essentials Damp Proof Integrated Extrusion | Essential Damp Proof luminaires with integrated LED module made of extrusion technology

### Areas of application

- Basements, garages, warehouses



### Product benefits

- Easy installation
- $\,-\,$  Suitable for use in dusty and damp outdoor locations thanks to high IP rating

### **Product features**

- Robust damp-proof luminaire made from the same mold
- Easy connectable cable gland



# TECHNICAL DATA

# Electrical data

Nominal wattage	18.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	140.000 mA
Inrush current time T <sub>h50</sub>	23 µs
Max. number of luminaires per miniature circuit breaker B16	42
Max. number of luminaires per miniature circuit breaker C10	34
Max. number of luminaires per miniature circuit breaker C16	54
Power factor $\lambda$	≥0.5
Total harmonic distortion	< 150 %
Protection class	II
Operating mode	Integrated LED driver

# Photometrical data

Luminous flux	2160 lm
Total luminous flux of contained light sources	2250 lm
Luminous efficacy	120 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	5 sdcm
Photobiological safety group acc. to EN62778	RG0
Beam angle	140 °

# Dimensions & Weight

Length	640.00 mm
Width	36.70 mm
Height	47.70 mm
Product weight	208.00 g



### Materials & Colors

Product color	White
Housing color	White
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Cable, 2-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK08
Dimmable	No
Mounting type	Surface
With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

# Additional product data

### **EQUIPMENT / ACCESSORIES**

- All required accessories included

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

# DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	DAMP PROOF ESSENTIAL EXTRUSION	
PDF	Legal information	Safety insert G11219279	
PDF	Declarations of conformity	DP ESSENTIAL EXTRUSION 840	
PDF	Declarations of conformity UKCA	DP ESSENTIAL EXTRUSION 840	

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854428777	Folding box	42 mm x 54 mm x 647 mm	225.00 g	1.47 dm <sup>3</sup>
4099854428784	Shipping box	675 mm x 135 mm x 120 mm	1752.00 g	10.94 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.