

PRODUCT DATASHEET Orbis Concrete 400MM 18W 830 Click Dim Gray

Orbis Concrete | LED ceiling luminaire with concrete ring



Areas of application

- Indoor
- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Stylish and modern design
- Long lifetime thanks to LED technology

Product features

- Type of protection: IP20
- Lifetime up to 30,000 h
- Click-DIM version: dimmable in three steps by repeated switching
- Housing material: concrete



TECHNICAL DATA

Electrical data


Nominal wattage	18.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	100.000 mA
Inrush current time T _{h50}	28.4 µs
Max. number of luminaires per miniature circuit breaker B16	139
Max. number of luminaires per miniature circuit breaker C10	86
Max. number of luminaires per miniature circuit breaker C16	139
Power factor λ	> 0.5
Total harmonic distortion	< 70 %
Protection class	II II
Operating mode	External LED driver

Photometrical data

Luminous flux	1500 lm
Luminous efficacy	83 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcm
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	116°

Dimensions & Weight

Diameter	400.00 mm
Height	100.00 mm
Product weight	4120.00 g



ORBIS CONCRETE 400 18W830 CLICKD

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Concrete
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	Yes
Type of dimming	3 DIM
Mounting type	Surface
Application environment	Indoor
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	15000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates Document name	
PDF	User instruction / safety instructions	ORBIS CONCRETE
PDF	Legal information	Safety insert G11219301
PDF	Declarations of conformity	ORBIS CONCRETE
PDF	Declarations of conformity UKCA	ORBIS CONCRETE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854446733	Folding box	144 mm x 450 mm x 450 mm	7310.00 g	29.16 dm³
4099854446740	Shipping box 2	468 mm x 306 mm x 475 mm	14620.00 g	68.02 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

PRODUCT DATASHEET Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.