# PRODUCT DATASHEET
# LS AY AC PLUG UK

POWER PLUGS FOR LED STRIP HIGH VOLTAGE 230V - UK | Power plug for LED strip 230V AC mains direct supply

## Areas of application

– General indoor illumination
– General outdoor illumination

## Product benefits

– Easy installation of connector, no manual wiring required

## Product features

– Power cable with integrated twist lock functionality and cable length of 1,50 m
– Only suitable for UK region
– Type of protection: IP20

# TECHNICAL DATA

### Electrical data

| | |
|---|---|
| Type of current | AC |

### Dimensions & Weight



| | |
|---|---|
| Length | 1570 mm |
| Width | 23 mm |
| Height | 23 mm |
| Product weight | 195.00 g |

### Colors & materials

| | |
|---|---|
| Product color | White |
| Body material | Polycarbonate (PC) |

### Temperatures & operating conditions

| | |
|---|---|
| Ambient temperature range | -20…+45 °C |
| Temperature range in operation | -20…+45 °C |
| Permitted rel. humidity during operation | 0…93 % |

### Additional product data

| | |
|---|---|
| Product remark | Available from September 2024 |

### Certificates & Standards

| | |
|---|---|
| Type of protection | IP20 |

# LOGISTICAL DATA

| | |
|---|---|
| Temperature range at storage | -20…+80 °C |

# DOWNLOAD DATA

| | Documents and certificates | Document name |
|---|---|---|
| PDF | User instruction / safety instructions | UI_LED STRIP_HV |

| | Documents and certificates | Document name |
|---|---|---|
| PDF | Legal information | Informationstext 18 Abs 4 ElektroG |
| PDF | Legal information | Safety Insert G11201420 |
| PDF | Declarations of conformity UKCA | LS LUM |

| | Tender texts | Document name |
|---|---|---|
| | Tender documents | POWER PLUGS FOR LED STRIP HIGH VOLTAGE 230V UK PLUG-en |

## LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---|---|---|---|---|
| 4058075844827 | BAG 1 | 200 mm x 250 mm x 50 mm | 211.00 g | 2.50 dm³ |
| 4058075844834 | Shipping box 50 | 357 mm x 357 mm x 264 mm | 11232.00 g | 33.65 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ADDITIONAL CATALOG INFORMATION



## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.