

PRODUCT DATASHEET LED Star Grow Lamp T 60 10W Clear E27

LED STAR GROW T LAMP | LED Grow Lamp for Indoor Plant Growth with 3 Light Spectrum Options



Areas of application

- Indoor applications: living area, green house or winter garden
- Outdoor use in outdoor luminaires only (minimum IP65)

Product benefits

- Special color spectrum which promotes growth of plants
- Adjustable for 3 different stages of flower and vegetable growth: Seeding, Growing, and Flowering
- Reduced green and yellow light to a level that plants can absorb, decreasing unnecessary energy consumption.

Product features

- LED grow light bulb
- Offering 3 different light spectrum options, adjustable via the integrated switch



TECHNICAL DATA

Electrical data

Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	220240 V
Operating mode	AC Mains
Nominal current	80 mA
Type of current	AC
Inrush current	1.5 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	103
Max. lamp number on MCB B16 A	166
Total harmonic distortion	120.14 %
Power factor λ	0.53

Photometrical data

Luminous flux	330 lm
Luminous efficacy	33 lm/W
Lumen main.fact.at end of nom.life time	0.96
Color rendering index Ra	80
Light color	8
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4

Light technical data

Beam angle	110°
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



0 "1 "	07.00
Overall length	97.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	48.00 g
Temperatures & operating conditions	
Ambient temperature range	-20+40 °C
Lifespan	
Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.96
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
Certificates & Standards	
Certificates & Standards Energy consumption	10.00 kWh/1000h
	10.00 kWh/1000h IP20
Energy consumption	
Energy consumption Type of protection	IP20
Energy consumption Type of protection Standards	IP20 LVD / EMC / RoHS / REACH
Energy consumption Type of protection Standards Photobiological safety group acc. to EN62778	IP20 LVD / EMC / RoHS / REACH
Energy consumption Type of protection Standards Photobiological safety group acc. to EN62778 Country-specific categorizations	IP20 LVD / EMC / RoHS / REACH RG1
Energy consumption Type of protection Standards Photobiological safety group acc. to EN62778 Country-specific categorizations Order reference	IP20 LVD / EMC / RoHS / REACH RG1
Energy consumption Type of protection Standards Photobiological safety group acc. to EN62778 Country-specific categorizations Order reference LOGISTICAL DATA	IP20 LVD / EMC / RoHS / REACH RG1 LEDS T60GROW 10
Energy consumption Type of protection Standards Photobiological safety group acc. to EN62778 Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage	IP20 LVD / EMC / RoHS / REACH RG1 LEDS T60GROW 10
Energy consumption Type of protection Standards Photobiological safety group acc. to EN62778 Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015	IP20 LVD / EMC / RoHS / REACH RG1 LEDS T60GROW 10 -20+80 °C
Energy consumption Type of protection Standards Photobiological safety group acc. to EN62778 Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used	IP20 LVD / EMC / RoHS / REACH RG1 LEDS T60GROW 10 -20+80 °C

Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Standby power	No
Networked standby power for CLS	No
Claim of equivalent power	No
Length	97.00 mm
Height	60.00 mm
Width	60.00 mm
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.832
LED light source replaces a fluorescent light source	No

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	On-Pack-Info	ELR - exempt lamps
PDF	Declarations of conformity	Grow lamps Classic T
PDF	Declarations of conformity UKCA	Grow lamp Classic T


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075845787	Folding box	60 mm x 60 mm x 145 mm	63.00 g	0.52 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075845794	Shipping box	205 mm x 140 mm x 117 mm	464.00 g	3.36 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.