

# PRODUCT DATASHEET

## Outdoor Flex 10M RGB IP65 Remote Control

OUTDOOR FLEX IP65 RGB | Robust and extendable LED Strip, RGB



---

### Areas of application

- Gardens and other outdoor areas
- Suitable for indoor and outdoor applications (IP65)

---

### Product benefits

- Bright, robust and durable

---

### Product features

- Extendable up to 50 meters, max. 450 W
- Protection class (strip): IP65
- Protection class (power supply): IP44
- RGB color control

TECHNICAL DATA

Electrical data


Nominal wattage	70.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor $\lambda$	> 0.90
Protection class	II

Photometrical data

Light color (designation)	Red / Green / Blue
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RG1
Beam angle	120 °

Dimensions & Weight

Length	10000.00 mm
Width	16.00 mm
Height	8.00 mm
Product weight	2780.00 g



OUTDOOR FLEX 10M RGB IP65  
RC

Materials & Colors

Product color	White
Housing color	White
Body material	Polyvinyl chloride (PVC)

Application & Mounting

Temperature range at storage	-20...+80 °C
Type of connection	Plug type F
Type of protection	IP65
Dimmable	Yes

Mounting type	Surface
Application environment	Outdoor
Replaceable light source	No

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	10000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### BATTERY

Battery size [GMS]	CR2025
--------------------	--------

### Certificates & Standards

Standards	CE
-----------	----



### EQUIPMENT / ACCESSORIES

- Equipped with 1.5 m cable and plug
- Cable reel for easy storage
- Remote control and battery included
- Mounting accessories included

### Safety advice

- Do not connect the rope light to the supply while it is wound onto a reel. Do not use the lightstrip when covered or recessed into a surface. The string of lights may not be operated within the packaging. Do not open the lightstrip.

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	Outdoor Flex UI/SI
	Declarations of conformity	Outdoor Flex RGB Declaration of Conformity CE

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075848788	Folding box 1	182 mm x 202 mm x 302 mm	2991.00 g	11.10 dm <sup>3</sup>
4058075848795	Shipping box 4	430 mm x 390 mm x 330 mm	12894.00 g	55.34 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.