

# PRODUCT DATASHEET LED Star Classic Stick 60 8.5W 827 Frosted E14

LED PCR CLASSIC STICK LAMP | LED lamps with recycled plastic



#### Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Attractive lamp appearance

#### **Product features**

- LED alternative to conventional lamps
- Good quality of light; color rendering index  $R_{a:} \ge 80$ ; constant chromaticity





#### TECHNICAL DATA

#### Electrical data

Nominal wattage	8.5 W
Construction wattage	8.50 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	60 W
Nominal current	60 mA
Type of current	AC
Inrush current	7.04 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	30
Max. lamp number on MCB B16 A	36
Total harmonic distortion	104.40 %
Power factor $\lambda$	0.63

#### Photometrical data

Luminous flux	806 lm
Luminous efficacy	94 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



LISO spectral power distribution 2700K CRI80 v1

# Light technical data

Beam angle	240 °
Warm-up time (60 %)	0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	120.00 mm
Diameter	37.00 mm
Maximum diameter	37 mm
Product weight	25.00 g

#### Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	90 °C

# Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

# Additional product data

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

# Capabilities

Dimmable	No	
Certificates & Standards		
Energy efficiency class	F <sup>1)</sup>	
Energy consumption	9.00 kWh/1000h	
Type of protection	IP20	
Standards	CE / UKCA / EAC	
Photobiological safety group acc. to EN62778	RG0	

Country-specific categorizations		
Order reference	LEDSSTICK60 8,5	
LOGISTICAL DATA		
Temperature range at storage	-40+80 °C	
Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	LED	

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.00 W
Claim of equivalent power	Yes
Length	120.00 mm
Height	37.00 mm
Width	37.00 mm
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90

Displacement factor	0.9125
LED light source replaces a fluorescent light source	No
EPREL ID	1402984,523289,1838209,2190118
Model number	AC31131,AC17508,AC55959,AC69375

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	LED Stick lamp
PDF	Declarations of conformity	LED CLASSIC / LED STICK
PDF	Declarations of conformity	Declaration of conformity CE
PDF	Declarations of conformity UKCA	LED CLASSIC / LED STICK
PDF	Declarations of conformity UKCA	UKCA declaration LED stick
	Photometric and lighting design files	Document name
	IES file (IES)	LEDSSTICK60 8W 827 FR OSRAM
	LDT file (Eulumdat)	AC08414_STICK60 8W 230VFR E14
	Light distribution curve type polar	LEDSSTICK75 8W 827 230VFR E14 BLI1 OSRAM
	Spectral power distribution	LISO spectral power distribution 2700K CRI80 v1

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075428362	Folding box	41 mm x 49 mm x 155 mm	40.00 g	0.31 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075585850	Shipping box 6	144 mm x 111 mm x 131 mm	327.00 g	2.09 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.