

PRODUCT DATASHEET DP BATTEN CBO EL CG 200V 3H MT AT

DAMP PROOF / BATTEN COMBO EMERGENCY KIT | Plug & Upgrade emergency kit for converting DAMP PROOF / BATTEN COMBO luminaires into emergency luminaires



Areas of application

- Suitable for DAMP PROOF / BATTEN COMBO

Product benefits

- Plug & Upgrade concept to extend the On/Off luminaire to an emergency luminaire
- Easy maintenance thanks to manual or self-test function of the emergency lighting
- Easy battery replacement possible

Product features

- Type of protection: IP20
- Impact resistance: IK06
- Operation mode: maintained (M) or non-maintained (NM)
- Battery technology: LiFePO4
- Ambient temperature in operation: 0...+40 °C


TECHNICAL DATA

Electrical data

Nominal wattage	3.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	23 mA
Inrush current	6.8 A
Power factor λ	> 0.3
Protection class	П

Dimensions & Weight

Length	217.00 mm
Width	44.00 mm
Height	31.00 mm
Product weight	219.00 g



DP BATTEN CBO EL CG 200V 3H MT AT

Materials & Colors

Product color	White
RAL Color (most similar)	RAL 9003
Body material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	0+40 °C
Temperature range at storage	-20+60 °C
Type of connection	Screwless terminal
Type of protection	IP20
Protection class IK (shock resistance)	IK06

Dimmable	No
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	40000 h ¹⁾
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

ECG lifetime	40000 h

BATTERY

Type of Battery	LiFePO4
Battery size [GMS]	Others

Emergency lighting

Type of emergency operation test	Manual
Wattage in maintained operation mode	3 W
Battery life in emergency operation mode	>3h

Certificates & Standards

Standards CE / CB / UKCA / EAC	Standards	CE / CB / UKCA / EAC
--------------------------------	-----------	----------------------

EQUIPMENT / ACCESSORIES

- Battery included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DP BATTEN CBO EL
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety Insert G11218810

	Documents and certificates	Document name
POF	Legal information	Legal Insert DP BATTEN CBO
PDF	Declarations of conformity	DP BATTEN CBO EL
POF	Declarations of conformity UKCA	DP BATTEN CBO

Tender texts	Document name
Tender documents	DAMP PROOF BATTEN COMBO EMERGENCY KIT EL CG 200V 3H MT AT-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854521430	Folding box 1	250 mm x 57 mm x 39 mm	247.00 g	0.56 dm ³
4099854521447	Shipping box 40	342 mm x 311 mm x 266 mm	10450.00 g	28.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.