

# PRODUCT DATASHEET SMART+ MATTER Tunable White Classic B40 4.9W E14

SMART+ MATTER Classic shapes Tunable white | Classic bulb shapes with Matter technology Tunable white



#### Areas of application

- General illumination through smart home technology
- Professional applications (hotels, bars, boutiques etc.) utilizing dynamic and robust ambient lighting effects
- When users want to mix and match smart home products from different manufacturers
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Wireless control via app or voice control
- Seamless integration with Matter-compatible systems
- Simplified set up process due to the standard user-friendly installation steps
- Enhanced security by implementing strong encryption and authentication protocols
- Lower energy consumption than incandescent or halogen lamps

#### **Product features**

- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0) or any other Matter-compatible platforms
- $-\,$  Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Dimmable
- Network protocol: Matter over WiFi
- Lifetime: up to 20,000 h
- Compatible with Alexa, Google Home, Apple Home and other Matter-compatible platforms






## TECHNICAL DATA

## Electrical data

Nominal wattage	4.9 W
Construction wattage	4.90 W
Nominal voltage	220240 V
Nominal current	42 mA
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor $\lambda$	0.50
Claimed equiv. conventional lamp power	40 W
Operating mode	AC Mains

## Photometrical data

Light color (designation)	Tunable White
Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	470 lm
Luminous flux	470 lm
Luminous efficacy	95 lm/W
Adjustable color temperature	27006500 K
Color temperature	27006500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4




Everlight 67-23ST KKE 2700K

# Light technical data

Beam angle	240 °
_	

Starting time	0.5 s
Warm-up time (60 %)	0.50 s

# Dimensions & Weight



Product weight	27.00 g
Diameter	39.00 mm
Maximum diameter	39 mm
Length	115.00 mm
Width	39.00 mm
Height	39.00 mm
Outer bulb [PICOS]	B40

## Lifespan

Number of switching cycles	100000
Lifespan	20000 h
Lumen maintenance at end of service lifetime	0.95

## Colors & materials

Product color	White
Housing color	White
Body material	Plastic

## Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

## Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E14

## Capabilities

Dimmable	Yes 1)
Compatible smart home technology	Amazon Alexa / Google Home / Apple Home / Samsung SmartThings

<sup>1) &</sup>lt;sub>Via App</sub>

#### Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	5.00 kWh/1000h
Standards	CE / UKCA
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E14
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	0 W
Networked standby power for CLS	<0.5 W

Claim of equivalent power	Yes
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	>0.5
LED light source replaces a fluorescent light source	No
EPREL ID	2240731
Model number	AC73908,AC73908

# Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### DOWNLOAD DATA

	Documents and certificates	Document name	
POF	Addon technical information	Wifi remote control compatibility list	
PDF	Addon technical information	Wifi remote control compatibility list (DE)	
POF	Extended installation guide	SMTMAT 230V	
PDF	Declarations of conformity	SMART MAT	
PDF	Declarations of conformity UKCA		
PDF	EU Data Act	SMART MATTER Lamps Luminaires Plugs	
	Photometric and lighting design files	Document name	
	Spectral power distribution	Everlight 67-23ST KKE 2700K	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854529924	Folding box	41 mm x 78 mm x 100 mm	52.00 g	0.32 dm <sup>3</sup>
4099854529931	Shipping box 4	164 mm x 90 mm x 116 mm	284.00 g	1.71 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.