

PRODUCT DATASHEET LED VALUE R

LED VALUE R LAMP | LED reflector lamps R63 and R80 with retrofit E27 screw base



Areas of application

- General lighting in residential spaces (living rooms, bedrooms, hallways)
- Accent lighting in retail and hospitality environments
- Suitable for use in open and enclosed fixtures
- Ideal for downlights, track lighting, and decorative luminaires

Product benefits

- Energy-efficient replacement for traditional halogen reflector lamps
- Long service life reduces maintenance and replacement costs
- Instant full brightness with no warm-up time
- Low heat emission enhances safety and comfort
- Environmentally friendly with no mercury content

Product features

- Retrofit design with standard E27 screw base
- $\,$ Available in R63 (4.8W) and R80 (8.5W) reflector formats
- Warm white light (2700K) for cosy and inviting ambience
- 36° beam angle for focused, directional lighting
- High luminous efficacy and consistent color rendering





TECHNICAL DATA

Electrical data

Nominal wattage	4.3 W
Construction wattage	4.30 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	38 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	0.40

Photometrical data

Luminous intensity	582 cd
Luminous flux	350 lm
Nominal useful luminous flux 90°	350 lm
Luminous efficacy	81 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	582 cd
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	101.50 mm
Diameter	63.00 mm
Maximum diameter	63 mm
Product weight	76.00 g

Temperatures & operating conditions

Rated lamp survival factor at 6,000 h

Ambient temperature range	-20+40 °C
Lifespan	
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70

≥ 0.90

Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Dimmable	No

Certificates & Standards

Energy efficiency class	F
Energy consumption	5.00 kWh/1000h
Type of protection	IP20
Photobiological safety group acc. to EN62778	RG1

Country-specific categorizations

Order ref	rence	LEDVR6360 4,8W/

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Correlated colour temperature type	SINGLE_VALUE
Length	101.50 mm
Height	63.00 mm
Width	63.00 mm
EPREL ID	522934,1368214
Model number	AC32667,AC45622

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
	. do. dg. 19 di iit (i 1000d, 01 iit)	Zimenere (lengar / maar / meigra,	G., GGG 11 G. G.	

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075797000	Folding box	65 mm x 65 mm x 107 mm	119.00 g	0.45 dm ³
4058075797017	Shipping box 10	357 mm x 147 mm x 125 mm	1325.00 g	6.56 dm ³
4099854367946	Shipping box 10	331 mm x 136 mm x 123 mm	1065.00 g	5.54 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.