

PRODUCT DATASHEET Spot Set Recess DIM 4.9W 827 120° Satin Nickel

LED Spot Set Recess DIM | Recess with integrated dimmable LED



Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Can be rotated and swiveled for optimum illumination
- Through-wiring possible with included connector box
- Easy mounting

Product features

- Recessed ceiling mounting
- Dimmable (with suitable Phase-cut dimmers)
- Adjustable swivel angle
- With integrated LED module and driver
- Color temperature: 2,700 K
- Through wiring possible
- Type of protection: IP20



Nickel

TECHNICAL DATA

Electrical data


Nominal wattage	4.90 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	33.000 mA
Inrush current	4.1 A
Max. number of luminaires per miniature circuit breaker B16	38
Max. number of luminaires per miniature circuit breaker C10	24
Max. number of luminaires per miniature circuit breaker C16	38
Power factor λ	0.40
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	200 lm	
Total luminous flux of contained light sources	420 lm	
Luminous efficacy	41 lm/W	
Color temperature	2700 K Warm White	
Light color (designation)		
Color rendering index Ra	80	
Standard deviation of color matching	6 sdcm	
Flickering metric (Pst LM)	<1	
Stroboscope effect metric (SVM)	< 0.4	
Photobiological safety group acc. to EN62778	RG1	
Beam angle	120 °	

Dimensions & Weight

Diameter	90.00 mm
Height	27.50 mm
Product weight	96.00 g



SP SETADJ 4.9W827 DIM 120DEG

Materials & Colors

Product color	Satin Nickel
Housing color	Satin Nickel
Body material	Aluminum Plastic
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Terminal, 2-Pole (L, N)	
Type of protection	IP20/IP20	
Protection class IK (shock resistance)	IK03	
Dimmable	Yes	
Type of dimming	PHASE CUT	
Mounting type	Recessed	
Mounting location	Ceiling	
Mounting diameter	75 mm	
Mounting depth	40 mm	
With light source	Yes	
Replaceable light source	No	

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	15000

¹⁾ _t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Emergency lighting

Type of emergency operation test	None
Certificates & Standards	

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Trouble formatt	Product remark	Available from November 2025
-----------------	----------------	------------------------------

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	Spotlights Adjustable 3x4.9W 827	
PDF	Declarations of conformity	Spotlights	
PDF	Declarations of conformity UKCA	Spotlights	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075853799	Folding box 3	94 mm x 202 mm x 103 mm	348.00 g	1.96 dm ³
4058075853805	Shipping box 24	392 mm x 216 mm x 231 mm	3242.00 g	19.56 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.