

# PRODUCT DATASHEET LED spot and downlight recess slim 85mm 4.5W 840 White

LED spot and downlight recess slim | Recess Slim Downlight with integrated Driver

## Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)



## Product benefits

- Excellent price/performance ratio
- Through-wiring possible with included connector box
- Easy mounting

### **Product features**

- Recessed ceiling mounting
- Color temperature: 4,000 K
- Through-wiring possible
- Type of protection: IP20



# TECHNICAL DATA

# Electrical data


Nominal wattage	4.50 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	60.000 mA
Power factor λ	> 0.7
Protection class	П
Operating mode	Mains voltage

# Photometrical data

Luminous flux	240 lm
Total luminous flux of contained light sources	480 lm
Luminous efficacy	53 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Beam angle	120 °

# Dimensions & Weight

	Diameter	85.00 mm
	Height	32.00 mm
Ī	Product weight	80.00 g



DL SLIM 85MM 4.5W 4000K 230V WT 6X3

## Materials & Colors

Product color	White
Housing color	White
Body material	Polyamide
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C

# Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	72 mm
Mounting depth	35 mm
With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
Number of switching cycles	50000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## **Emergency lighting**

Type of emergency operation test	None

## Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

# Additional product data

Product remark	Available from October 2025

## Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

### **DOWNLOAD DATA**

Documents and certificates		Document name	
PDF	User instruction / safety instructions	DL SLIM	
Declarations of conformity  CE Declaration Downlight Slim		CE Declaration Downlight Slim	
PDF	Declarations of conformity UKCA	UKCA Declaration Downlight Slim	

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075853874	Folding box 3	113 mm x 163 mm x 108 mm	356.00 g	1.99 dm³
4058075853881	Shipping box 18	355 mm x 182 mm x 247 mm	2224.00 g	15.96 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.