

PRODUCT DATASHEET LED Downlight Side-Mainlight 175mm 18W 830 White

LED Downlight Side-Mainlight | Downlight with selectable light sources



Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Through-wiring possible with included connector box
- Easy mounting

Product features

- Recessed ceiling mounting
- Color temperature: 3,000 K
- Through wiring possible
- Type of protection: IP20

TECHNICAL DATA

Electrical data


Nominal wattage	18.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	450.000 mA
Max. number of luminaires per miniature circuit breaker B16	23
Max. number of luminaires per miniature circuit breaker C16	23
Power factor λ	> 0.90
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	1400 lm
Total luminous flux of contained light sources	1400 lm
Luminous efficacy	77 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °

Dimensions & Weight

Diameter	175.00 mm
Height	30.00 mm
Product weight	350.00 g



DL SLIM175 RD ADJ SIDE-MAIN 830 WT

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+70 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20/IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Mounting diameter	85145 mm
Mounting depth	30,0 mm
With light source	Yes
Replaceable light source	No

Lifespan

Number of switching cycles 5000	0000
---------------------------------	------

Emergency lighting

Type of emergency operation test None		Type of emergency operation test	None
---------------------------------------	--	----------------------------------	------

Certificates & Standards

Standards	CE

Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark	Available from October 2025

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	DL SLIM	
Declarations of conformity		CE Declaration Downlight Adjustable	
Declarations of conformity UKCA		UKCA Declaration Downlight Adjustable	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075853935	Folding box 1	43 mm x 183 mm x 183 mm	459.00 g	1.44 dm ³
4058075853942	Shipping box 24	386 mm x 276 mm x 392 mm	11624.00 g	41.76 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.