


# PRODUCT DATASHEET

## LED Spot Stamp 2xGU10 White and Wood

LED Spot Stamp | Ceiling mounted luminaires made with mixed materials with adjustable GU10 spotlights



---

### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, bedrooms, basements

---

### Product benefits

- Flexible thanks to replaceable LED lamps
- Easy mounting

---

### Product features

- Luminaire family features four versions with up to 4 spot heads
- Housing material: metal and wood
- On/off switch on 1-head version for easy operation
- Adjustable heads




## TECHNICAL DATA

### Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

### Dimensions & Weight

Length	255.00 mm
Width	90.00 mm
Height	148.00 mm
Product weight	485.00 g



LED SPOT STAMP 2XGU10 WT

### Materials & Colors

Product color	White Wood decor
Housing color	White Wood decor
Body material	Steel Rubberwood
Glow Wire Test according to IEC 60695-2-12	650 °C

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
Adjustable	Yes

With light source	No
Replaceable light source	No
Holder designation	GU10

**Emergency lighting**

Type of emergency operation test	None
----------------------------------	------

**Certificates & Standards**

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

**Additional product data**

Product remark	Maximum bulb wattage: 5 W LED / Available from October 2025
Number of illuminants	2

**Safety advice**

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

**DOWNLOAD DATA**

Documents and certificates		Document name
	User instruction / safety instructions	LED SPOT STAMP G11238937
	Declarations of conformity	LED SPOT CE declaration

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075852600	Folding box 1	112 mm x 172 mm x 302 mm	664.00 g	5.82 dm <sup>3</sup>
4058075852617	Shipping box 4	365 mm x 245 mm x 325 mm	3106.00 g	29.06 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.