

PRODUCT DATASHEET DULUX LED S/E7 AC MAINS VALUE 3.5W 865 2G7

DULUX LED S/E AC MAINS VALUE | LED replacement for CFLni with 4-pin 2G7 base for AC mains operation



Areas of application

- General illumination within ambient temperatures from -20...+45 $^{\circ}\text{C}$
- Offices, public buildings
- Shops
- Hotels, restaurants
- Walkways and corridors

Product benefits

- Operation directly on 230 V AC mains possible
- Not suitable for operation with conventional control gear (CCG)
- Not suitable for operation with electronic control gear (ECG)
- Easy installation
- Low energy consumption
- Easy relamping thanks to compact design

Product features

- LED replacement for conventional compact fluorescent lamps for use on AC mains
- Lifetime up to 30,000 h
- Single-ended four-pin plug-in 2G7 base
- Type of protection: IP20
- Mercury-free lamps





TECHNICAL DATA

Electrical data

Nominal wattage	3.5 W
Construction wattage	3.50 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	7 W
Nominal current	16 mA
Type of current	AC
Inrush current	11.2 A
Suitable for DC input	Yes
Input voltage DC	186270 V ¹⁾
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	53
Max. lamp number on MCB B16 A	67
Total harmonic distortion	≤ 20 %
Power factor λ	> 0.90

¹⁾ Permitted voltage range

Photometrical data

Luminous flux	400 lm
Luminous efficacy	114 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



EPREL data spectral diagram PROF LEDr 6500K

Light technical data

Beam angle	130 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	120.00 mm
Product weight	34.00 g

Temperatures & operating conditions

Ambient temperature range	-20+45 °C ¹⁾
Maximum temperature at tc test point	82 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.96
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	2G7

Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	Available from December 2025

Capabilities

Dimmable	No

Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	4.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG0

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations

Temperature range at storage

Order reference	DULUX LED S/E7
LOGISTICAL DATA	

-20...+80 °C

Energy labelling regulation data acc EU 2019/2015

LE_VALUE
0 mm
nm

Chromaticity coordinate x Chromaticity coordinate y 0.328 R9 Colour rendering index 1 Beam angle correspondence SPHERE_360 Survival factor 0.90 Displacement factor 0.90 LED light source replaces a fluorescent light source No	32 mm
R9 Colour rendering index 1 Beam angle correspondence SPHERE_360 Survival factor 0.90 Displacement factor 0.90	0.312
Beam angle correspondence SPHERE_360 Survival factor 0.90 Displacement factor 0.90	0.328
Survival factor 0.90 Displacement factor 0.90	1
Displacement factor 0.90	SPHERE_360
· ·	0.90
LED light source replaces a fluorescent light source No	0.90
	orescent light source No
EPREL ID 2416882	2416882
Model number AC85411	AC85411

Safety advice

- Not suitable for operation with conventional control gear.
- Not suitable for operation with electronic control gear.
- The operating temperature range of DULUX LED is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- All electrical connections must be made by a qualified person.
- Lamp not suitable for emergency operation.
- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	DULUX LED SE	
POF	Extended installation guide	LEDVANCE Luminaire conversion checklist	
POF	Declarations of conformity	CE DULUX LED SE	
POF	Declarations of conformity UKCA	UKCA DULUX LED SE	
	Photometric and lighting design files	Document name	
	IES file (IES)	DULUX LED S E7 AC V 3.5W 865 2G7 LEDV	
	LDT file (Eulumdat)	DULUX LED S E7 AC V 3.5W 865 2G7 LEDV	

UGR file (UGR table) DULUX LED S E7 AC V 3.5W 865 2G7 LEDV Light distribution curve type cone DULUX LED S E7 AC V 3.5W 865 2G7 LEDV DULUX LED S E7 AC V 3.5W 865 2G7 LEDV	Photometric and lighting design files	Document name
	UGR file (UGR table)	DULUX LED S E7 AC V 3.5W 865 2G7 LEDV
Light distribution curve type polar DULUX LED S E7 AC V 3.5W 865 2G7 LEDV	Light distribution curve type cone	DULUX LED S E7 AC V 3.5W 865 2G7 LEDV
	Light distribution curve type polar	DULUX LED S E7 AC V 3.5W 865 2G7 LEDV
Spectral power distribution EPREL data spectral diagram PROF LEDr 6500K	Spectral power distribution	EPREL data spectral diagram PROF LEDr 6500K

Tender texts	Document name
Tender documents	DULUX LED S E AC MAINS VALUE 3.5W 865 2G7-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854669859	Folding box 1	24 mm x 40 mm x 125 mm	43.00 g	0.12 dm ³
4099854669866	Shipping box 10	131 mm x 89 mm x 139 mm	490.00 g	1.62 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.