

# PRODUCT DATASHEET Tracklight Spot Beam 4.8W 830 Black

Tracklight Spot Cylinder Gold | Tracklight Spot LED Integrated



## Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)

#### Product benefits

- Spots adjustable in any direction
- Timeless design

#### Product features

- Adjustable swivel angle
- Color temperature: 3,000 K
- Easy operation and installation



## TECHNICAL DATA

## Electrical data


Nominal wattage	4.80 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	23.000 mA
Power factor $\lambda$	0.50
Total harmonic distortion	70 %
Protection class	П
Operating mode	Mains voltage

#### Photometrical data

Luminous flux	300 lm
Total luminous flux of contained light sources	450 lm
Luminous efficacy	63 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1

# Dimensions & Weight

Length	90.00 mm
Width	94.00 mm
Height	132.00 mm
Product weight	210.00 g



TRACKLIGHT SPOT BEAM 4.8W

## Materials & Colors

Product color	Black
Housing color	Black
Body material	Polycarbonate (PC)/Wood/Metal
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

# Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
With light source	Yes
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> \_t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# **Emergency lighting**

Type of emergency operation test	None
Certificates & Standards	

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

# Additional product data

Product remark Available from December 2025
---

#### Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

#### **DOWNLOAD DATA**

	Documents and certificates Document name	
PDF	User instruction / safety instructions	Tracklight Spot Beam

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854631245	Folding box 1	100 mm x 100 mm x 120 mm	259.00 g	1.20 dm <sup>3</sup>
4099854631252	Shipping box 4	210 mm x 110 mm x 250 mm	1154.00 g	5.78 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.