

PRODUCT DATASHEET Orbis Ghost 380mm 40W CCT White

Orbis Ghost | LED ceiling lamp with homogeneous diffusion



Areas of application

- Indoor
- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Color temperature adjustment for different application needs

Product features

- Color temperature slider (CTS): 2700 K, 4000 K, 6500 K



TECHNICAL DATA

Electrical data


Nominal wattage	40.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz
Nominal current	200.000 mA
Inrush current	7 A
Inrush current time T _{h50}	100 μs
Max. number of luminaires per miniature circuit breaker B16	64
Max. number of luminaires per miniature circuit breaker C10	32
Max. number of luminaires per miniature circuit breaker C16	50
Power factor λ	> 0.9
Total harmonic distortion	< 20 %
Protection class	II II
Operating mode	Mains voltage

Photometrical data

Luminous flux	3200 lm
Total luminous flux of contained light sources	4700 lm
Luminous efficacy	80 lm/W
Color temperature	2700 K / 4000 K / 6500 K
Reference control setting of contained light source (Kelvin)	2700 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	120 °

Dimensions & Weight

Diameter	380.00 mm
Height	61.00 mm
Product weight	630.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	STEEL ACRYLIC
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
With light source	Yes
Replaceable light source	No

Lifespan

Emergency lighting

31 0 3 1

Certificates & Standards

Standards	CE / UKCA

Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	ORBIS GHOST_BRUSH	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854659003	Folding box	102 mm x 422 mm x 423 mm	960.00 g	18.21 dm ³
4099854659010	Shipping box 4	438 mm x 424 mm x 448 mm	5010.00 g	83.20 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.