

# PRODUCT DATASHEET

## LED Spot Cup 1xG9 Brushed Nickel

LED Spot Cup | Ceiling mounted luminaires with adjustable G9 spotlights



### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, bedrooms, basements

### Product benefits

- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

### Product features

- Luminaire family features four versions with up to 4 spot heads
- Housing surface made of brushed nickel
- Diffuser made of alabaster glass
- Adjustable head




TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

Dimensions & Weight

Length	90.00 mm
Width	150.00 mm
Height	105.00 mm
Product weight	265.00 g



LED SPOT CUP 1XG9

Materials & Colors

Product color	Brushed nickel
Housing color	Brushed nickel
Body material	Steel
Cover material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall

Adjustable	Yes
With light source	No
Replaceable light source	No
Holder designation	G9

### Emergency lighting

Type of emergency operation test	None
----------------------------------	------

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No



### Additional product data

Product remark	Maximum bulb wattage: 5 W LED / Available from October 2025
Number of illuminants	1

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LED SPOT CUP G11238935
	Declarations of conformity	LED SPOT CE declaration

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075852402	Folding box 1	102 mm x 127 mm x 117 mm	401.00 g	1.52 dm <sup>3</sup>
4058075852419	Shipping box 4	280 mm x 225 mm x 140 mm	1849.00 g	8.82 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.