

# PRODUCT DATASHEET ENDURA Style Lantern Modern 12W

ENDURA® Style Lantern Modern | Contemporary lanterns with light guide for low-glare illumination



#### Areas of application

- Outdoor use (IP54)
- Building facades
- Gardens, balconies and other outdoor areas
- Pathway lighting
- Driveways

#### Product benefits

- Energy-efficient thanks to LED technology
- Easy and quick installation

#### **Product features**

- Very bright and functional outdoor LED luminaires
- Die-cast aluminum housing
- Available as wall and bollard luminaires



# TECHNICAL DATA

# Electrical data


Nominal wattage	12.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	65.000 mA	
Max. number of luminaires per miniature circuit breaker B16	20	
Max. number of luminaires per miniature circuit breaker C16	28	
Power factor λ	> 0.5	
Total harmonic distortion	≤ 70 %	
Protection class	I	
Operating mode	Mains voltage	

## Photometrical data

Luminous flux	610 lm
Total luminous flux of contained light sources	900 lm
Luminous efficacy	50 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	≤6 sdcm
Photobiological safety group acc. to EN62778	RG0
Beam angle	360 °

# Dimensions & Weight

Length	176.00 mm
Width	110.00 mm
Height	240.00 mm
Product weight	1300.00 g



## Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+85 °C
Type of connection	Screw terminal
Type of protection	IP44
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

Standards	CE / UKCA / EAC
Luminaire with limited surface temperature, "D sign"	No

## Additional product data

Number of illuminants empty
-----------------------------

#### **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

# Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	User instruction / safety instructions	ENDURA STYLE LANTERN MODERN WALL
PDF	Legal information	Safety insert G11219578
PDF	Declarations of conformity	ENDURA STYLE LUM
PDF	Declarations of conformity UKCA	Fixed LUM

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854453335	Folding box 1	134 mm x 204 mm x 296 mm	1630.00 g	8.09 dm <sup>3</sup>
4099854453342	Shipping box 4	425 mm x 285 mm x 315 mm	6520.00 g	38.15 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.