

PRODUCT DATASHEET P CLAS A 75 10.5 W/2700 K E27

PARATHOM® CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design

Product features

- Professional LED lamps for line voltage
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- $-\,$ Long lifetime up to 25,000 h
- Good quality of light; color rendering index $R_{a:} \geq$ 80; constant chromaticity





TECHNICAL DATA

Electrical data

Nominal wattage	10.5 W
Construction wattage	10.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	70 mA
Type of current	AC
Inrush current	5 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	70
Max. lamp number on MCB B16 A	120
Power factor λ	> 0.70

Photometrical data

Luminous intensity	- cd
Luminous flux	1055 lm
Nominal useful luminous flux 90°	1055 lm
Luminous efficacy	100 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	220 °
Warm-up time (60 %)	< 1.00 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	110.00 mm
Diameter	60.00 mm

Maximum diameter	60 mm	
Product weight	43.00 g	
emperatures & operating conditions		
Ambient temperature range	-20+40 °C	
Maximum temperature at tc test point	100 °C	
ifespan		
Number of switching cycles	100000	
Lumen maintenance at end of service lifetime	0.70	
Rated lamp survival factor at 6,000 h	≥ 0.90	
Additional product data		
Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Design / version	Frosted	
Product remark	All technical parameters apply to the entire lamp / Due to the comproduction process for light-emitting diodes, the typical values sho for the technical LED parameters are purely statistical values that continuous not necessarily match the actual technical parameters of each individual product, which can vary from the typical value / LED lam contain several electronic components. Under unfavourable condit these can lead to acoustic noise. In case of resonance even low no can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoust resonance effect) as well as the dimmer or the transformer (harmon or electronic resonance)	
Capabilities		
Dimmable	Yes	
Certificates & Standards		
Energy efficiency class	F 1)	
Energy consumption	11.00 kWh/1000h	
Type of protection	IP20	
Standards	CE / ROHS / ERP	
Photobiological safety group acc. to EN62778	RG1	

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

Order	reference	LEDPCLA75D 10,5
Energy	abelling regulation data acc EU 2019/2015	
Light	source cap-type (or other electric interface)	E27
Correl	lated colour temperature type	SINGLE_VALUE
Lengtl	h	110.00 mm
Heigh	t	60.00 mm
Width		60.00 mm

1403220

AC24704

LOGISTICAL DATA

EPREL ID

Model number

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075462595	Folding box 1	61 mm x 61 mm x 109 mm	57.00 g	0.41 dm ³
4058075462601	Shipping box 10	318 mm x 133 mm x 124 mm	688.00 g	5.24 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.