

PRODUCT DATASHEET

P CLAS A 40 FR 5 W/2700 K E27

PARATHOM® CLASSIC A DIM | Dimmable LED lamps, classic bulb shape



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Lower energy consumption than incandescent or halogen lamps
- Robust against vibrations
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs

Product features

- Professional LED lamps for line voltage
- Beam angle: up to 300°
- Dimmable
- Base: E27, B22d



- Lifetime up to 15,000 h
- Lamp made of glass
- Good quality of light; color rendering index $R_a \geq 80$; constant chromaticity

TECHNICAL DATA

Electrical data

| | |
|--|-------------|
| Nominal wattage | 5 W |
| Construction wattage | 5.00 W |
| Nominal voltage | 220...240 V |
| Claimed equiv. conventional lamp power | 40 W |
| Nominal current | 25 mA |
| Type of current | AC |
| Inrush current | 2.8 A |
| Operating frequency | 50...60 Hz |
| Mains frequency | 50...60 Hz |
| Max. lamp number on MCB B10 A | 100 |
| Max. lamp number on MCB B16 A | 150 |
| Power factor λ | > 0.70 |

Photometrical data

| | |
|---|------------|
| Luminous flux | 470 lm |
| Nominal useful luminous flux 90° | 470 lm |
| Luminous efficacy | 94 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | ≥80 |
| Light color | 827 |
| Standard deviation of color matching | ≤6 sdcn |
| Rated LLMF at 6,000 h | 0.80 |

Light technical data

| | |
|---------------------|----------|
| Beam angle | 320 ° |
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight

| | |
|------------------|-----------|
| Overall length | 105.00 mm |
| Diameter | 60.00 mm |
| Maximum diameter | 60 mm |

| | |
|----------------|---------|
| Product weight | 32.00 g |
|----------------|---------|

Temperatures & operating conditions

| | |
|--------------------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Maximum temperature at tc test point | 50 °C |

Lifespan

| | |
|--|--------|
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service lifetime | 0.70 |
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |

Additional product data

| | |
|-----------------------------|--|
| Base (standard designation) | E27 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Frosted |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value / LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance) |

Capabilities

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & Standards

| | |
|--|----------------|
| Energy efficiency class | F 1) |
| Energy consumption | 5.00 kWh/1000h |
| Type of protection | IP20 |
| Standards | CE |
| Photobiological safety group acc. to EN62778 | RG0 |

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | LEDPCLA40D 5W/8 |
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|---|--------------|
| Light source cap-type (or other electric interface) | E27 |
| Correlated colour temperature type | SINGLE_VALUE |
| Length | 105.00 mm |
| Height | 60.00 mm |
| Width | 60.00 mm |
| EPREL ID | 1403372 |
| Model number | AC24285 |

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075439399 | Folding box 1 | 60 mm x 60 mm x 111 mm | 46.00 g | 0.40 dm ³ |
| 4058075439405 | Shipping box 10 | 325 mm x 136 mm x 126 mm | 532.00 g | 5.57 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.