

# PRODUCT DATASHEET ST CLAS B 40 5.5 W/4000 K E14

LED STAR CLASSIC B | LED lamps, classic mini-candle shape



#### Areas of application

- Domestic applications
- General illumination
- Chandeliers
- Outdoor use in suitable outdoor luminaires only

## Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

## Product features

- LED alternative to conventional lamps
- Mercury-free lamps





## TECHNICAL DATA

## Electrical data

Nominal wattage	5.5 W
Construction wattage	5.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	43 mA
Type of current	AC
Inrush current	10 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	287
Max. lamp number on MCB B16 A	461
Power factor $\lambda$	> 0.50


## Photometrical data

Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	85 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight



Overall length	100.00 mm
Diameter	37.00 mm
Maximum diameter	37 mm
Product weight	20.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	92.3 °C

# Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	E14	
Mercury content	0.0 mg	
Mercury-free	Yes	
Design / version	Frosted	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value / In development, data preliminary	

## Capabilities

#### Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	6.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

## Country-specific categorizations

ILCOS	DRBB/F-5-220-240-E14-35
Order reference	LEDSCLB40 5,5W/

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E14
Correlated colour temperature type	SINGLE_VALUE
Length	100.00 mm
Height	37.00 mm
Width	37.00 mm
Displacement factor	0.5
EPREL ID	1403232
Model number	AC24718

## Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899962057	Blister 1	42 mm x 140 mm x 120 mm	35.00 g	0.71 dm <sup>3</sup>
4052899962545	Shipping box	262 mm x 153 mm x 132 mm	282.00 g	5.29 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.