

PRODUCT DATASHEET LED Value PAR16 80 60° 6.9W 840 GU10

LED VALUE PAR16 | LED reflector lamps PAR16 with retrofit pin base



Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Lower energy consumption than incandescent or halogen lamps

Product features

- LED alternative to high voltage halogen lamps
- Not dimmable
- Base: GU10
- Lamp made of glass
- Good quality of light; color rendering index CRI ≥ 80






TECHNICAL DATA

Electrical data

Nominal wattage	6.9 W
Construction wattage	6.90 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	80 W
Nominal current	50 mA
Type of current	AC
Inrush current	4.84 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	116
Max. lamp number on MCB B16 A	184
Total harmonic distortion	150 %
Power factor λ	> 0.50

Photometrical data

Luminous intensity	750 cd
Luminous flux	575 lm
Nominal useful luminous flux 90°	575 lm
Luminous efficacy	83 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	750 cd
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



OS S10x18 4000K

Light technical data

Beam angle	60 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	54.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	39.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	97.5 °C

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg
Mercury-free	Yes

Product remark	All technical parameters apply to the entire lamp / Due to the complete production process for light-emitting diodes, the typical values show for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Capabilities		
Dimmable	No	
Certificates & Standards		
Energy efficiency class	F 1)	
Energy consumption	7.00 kWh/1000h	
Type of protection	IP20	
Standards	CE / UKCA / EAC	
Photobiological safety group acc. to EN62778	RG1	
Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lower country-specific categorizations Order reference		
	est efficiency)	
	LVPAR168060 6,9	
Country-specific categorizations		
Country-specific categorizations Order reference		
Country-specific categorizations Order reference OGISTICAL DATA	LVPAR168060 6,9	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage	LVPAR168060 6,9	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015	LVPAR168060 6,9 -20+80 °C	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used	LVPAR168060 6,9 -20+80 °C	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional	LVPAR168060 6,9 -20+80 °C LED DLS	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains	LVPAR168060 6,9 -20+80 °C LED DLS MLS	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface)	LVPAR168060 6,9 -20+80 °C LED DLS MLS GU10	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	LVPAR168060 6,9 -20+80 °C LED DLS MLS GU10 No	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source	LVPAR168060 6,9 -20+80 °C LED DLS MLS GU10 No No	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope	LVPAR168060 6,9 -20+80 °C LED DLS MLS GU10 No No	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source	LVPAR168060 6,9 -20+80 °C LED DLS MLS GU10 No No No No	
Country-specific categorizations Order reference OGISTICAL DATA Temperature range at storage Inergy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source Anti-glare shield	LVPAR168060 6,9 -20+80 °C LED DLS MLS GU10 No No No No No	

54.00 mm

50.00 mm

Length

Height

Width	50.00 mm
Chromaticity coordinate x	0.3818
Chromaticity coordinate y	0.3797
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0.90
Displacement factor	0.70
LED light source replaces a fluorescent light source	No
EPREL ID	522981,1368242,1841993
Model number	AC32748,AC45670,AC57947,AC57947,AC57947

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA				
	Documents and certificates	Document name		
PDF	Declarations of conformity	LED SPOT PAR16		
PDF	Declarations of conformity	LED PA16		
PDF	Declarations of conformity UKCA	LED PAR16		
	Dhotomotrio and lighting decign files	Document name		
	Photometric and lighting design files	Document name		
	Photometric and lighting design files IES file (IES)	AC08575_PAR16 6,9W230V		
	IES file (IES)	AC08575_PAR16 6,9W230V		

Light distribution curve type cone

Light distribution curve type polar Light distribution curve type polar LVPAR168060 6,9W 840 230V GU10 FS1 OSRAM

LVPAR168060 6,9W 840 230V GU10 FS1 OSRAM

PAR16 M3 80 60 4000K GU10

Photometric and lighting design files	Document name
Spectral power distribution	OS S10x18 4000K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075096783	Folding box	52 mm x 52 mm x 60 mm	46.00 g	0.16 dm ³
4058075096790	Shipping box 10	270 mm x 114 mm x 72 mm	510.00 g	2.22 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.