

PRODUCT DATASHEET LED Value PAR16 80 36° 6.9W 830 GU10

LED VALUE PAR16 | LED reflector lamps PAR16 with retrofit pin base



Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Lower energy consumption than incandescent or halogen lamps

Product features

- LED alternative to high voltage halogen lamps
- Not dimmable
- Base: GU10
- Lamp made of glass
- Good quality of light; color rendering index CRI ≥ 80






TECHNICAL DATA

Electrical data

Nominal wattage	6.9 W
Construction wattage	6.90 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	80 W
Nominal current	50 mA
Type of current	AC
Inrush current	4.84 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	116
Max. lamp number on MCB B16 A	184
Total harmonic distortion	150 %
Power factor λ	> 0.50

Photometrical data

Luminous intensity	860 cd	
Luminous flux	575 lm	
Nominal useful luminous flux 90°	575 lm	
Luminous efficacy	83 lm/W	
Lumen main.fact.at end of nom.life time	0.93	
Light color (designation)	Warm White	
Color temperature	3000 K	
Color rendering index Ra	80	
Light color	830	
Standard deviation of color matching	≤6 sdcm	
Rated peak intensity	860 cd	
Flickering metric (Pst LM)	1.0	
Stroboscope effect metric (SVM)	0.4	



OS S10x18 3000K

Light technical data

Beam angle	36 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	54.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	39.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	97.5 °C

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	GU10
Mercury content	0.0 mg
Mercury-free	Yes

No F 1) 7.00 kWh/1000h IP20 CE / UKCA / EAC RG1	
F ¹⁾ 7.00 kWh/1000h IP20 CE / UKCA / EAC	
7.00 kWh/1000h IP20 CE / UKCA / EAC	
7.00 kWh/1000h IP20 CE / UKCA / EAC	
IP20 CE / UKCA / EAC	
CE / UKCA / EAC	
RG1	
-20+80 °C	
LED	
DLS	
MLS	
GU10	
No	
SINGLE_VALUE	
SIIVALL_VALUL	
0 W	

54.00 mm

50.00 mm

Length

Height

Width	50.00 mm	
Chromaticity coordinate x	0.4338	
Chromaticity coordinate y	0.4030	
R9 Colour rendering index	1	
Beam angle correspondence	NARROW_CONE_90	
Survival factor	0.9	
Displacement factor	0.70	
LED light source replaces a fluorescent light source	No	
EPREL ID	522985,734489,1368238,1841989,2505771	
Model number	AC32743,AC35479,AC45666,AC57943,AC57943,AC57943,AC91854	

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	LED SPOT PAR16	
PDF	Declarations of conformity	LED PA16	
POF	Declarations of conformity UKCA	LED PAR16	
	Photometric and lighting design files	Document name	
(ES)	IES file (IES)	AC08571_PAR16 6	
	IES file (IES)	M3 80 36 3000K GU10	
	LDT file (Eulumdat)	AC08571_PAR16 6	
	LDT file (Eulumdat)	M3 80 36 3000K GU10	
	Light distribution curve type cone	LVPAR168036 6,9W 830 230V GU10 FS1 OSRAM	
	Light distribution curve type polar	LVPAR168036 6,9W 830 230V GU10 FS1 OSRAM	
	Light distribution curve type polar	M3 80 36 3000K GU10	

Photometric and lighting design files	Document name
Spectral power distribution	OS S10x18 3000K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075096646	Folding box	52 mm x 52 mm x 60 mm	46.00 g	0.16 dm ³
4058075096653	Shipping box 10	270 mm x 114 mm x 72 mm	510.00 g	2.22 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.