

PRODUCT DATASHEET LED Value PAR16 80 60° 6.9W 830 GU10

LED VALUE PAR16 | LED reflector lamps PAR16 with retrofit pin base



Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Lower energy consumption than incandescent or halogen lamps

Product features

- LED alternative to high voltage halogen lamps
- Not dimmable
- Base: GU10
- Lamp made of glass
- Good quality of light; color rendering index CRI ≥ 80






TECHNICAL DATA

Electrical data

Nominal wattage	6.9 W
Construction wattage	6.90 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	80 W
Nominal current	50 mA
Type of current	AC
Inrush current	4.84 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	116
Max. lamp number on MCB B16 A	184
Total harmonic distortion	150 %
Power factor λ	> 0.50

Photometrical data

Luminous intensity	700 cd
Luminous flux	575 lm
Nominal useful luminous flux 90°	575 lm
Luminous efficacy	83 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	80
Light color	830
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	700 cd
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



OS S10x18 3000K

Light technical data

Beam angle	60 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	54.00 mm
Diameter	50.00 mm
Maximum diameter	50 mm
Product weight	39.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	97.5 °C

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	GU10	
Mercury content	0.0 mg	
Mercury-free	Yes	

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Capabilities		
Dimmable	No	
Certificates & Standards		
Energy efficiency class	F 1)	
Energy consumption	7.00 kWh/1000h	
Type of protection	IP20	
Standards	CE / UKCA / EAC	
Photobiological safety group acc. to EN62778	RG1	
Order reference LOGISTICAL DATA	LVPAR168060 6,9	
LOGISTICAL DATA		
Temperature range at storage	-20+80 °C	
Energy labelling regulation data acc EU 2019/2015		
Lighting technology used	LED	
Non-directional or directional	DLS	
Mains or non-mains	MLS	
Light source cap-type (or other electric interface)	GU10	
Connected light source (CLS)	No	
Color-tuneable light source	No	
Envelope	No	
High luminance light source	No	
Anti-glare shield	No	
Correlated colour temperature type	SINGLE_VALUE	
Standby power	o w	
Claim of equivalent power	Yes	
Length	54.00 mm	

50.00 mm

Height

Width	50.00 mm
Chromaticity coordinate x	0.4338
Chromaticity coordinate y	0.4030
R9 Colour rendering index	1
Beam angle correspondence	NARROW_CONE_90
Survival factor	0.9
Displacement factor	0.70
LED light source replaces a fluorescent light source	No
EPREL ID	522982,1368241,1841992
Model number	AC32747,AC45669,AC57946,AC57946,AC57946

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA				
	Documents and certificates	Document name		
PDF	Declarations of conformity	LED SPOT PAR16		
POF	Declarations of conformity	LED PA16		
PDF	Declarations of conformity UKCA	LED PAR16		
	Photometric and lighting design files	Document name		
	Photometric and lighting design files IES file (IES)	AC08574_PAR16 6,9W230V		
	IES file (IES)	AC08574_PAR16 6,9W230V		

Light distribution curve type cone
Light distribution curve type polar

Light distribution curve type polar

LVPAR168060 6,9W 830 230V GU10 FS1 OSRAM

LVPAR168060 6,9W 830 230V GU10 FS1 OSRAM

LED PAR16 80 60 P 3000K GU10

Photometric and lighting design files	Document name
Spectral power distribution	OS S10x18 3000K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075096769	Folding box	52 mm x 52 mm x 60 mm	46.00 g	0.16 dm ³
4058075096776	Shipping box 10	270 mm x 114 mm x 72 mm	510.00 g	2.22 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.