

PRODUCT DATASHEET LED PFM CLAS A FIL 8.5 W/6500 K B22d

LED PERFORMANCE CLASSIC A FILAMENT | LED lamps, classic bulb shape, dimmable



Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Good quality of light
- Reliable operation thanks to brand quality

Product features

- Beam angle: up to 300°
- Long lifetime up to 15,000 h
- Color rendering index Ra: ≥ 80
- High color consistency: < 6 SDCM
- Luminous efficacy: up to 124 lm/W
- Same appearance like conventional light bulb shape



- Mercury-free lamps
- Dimmable

TECHNICAL DATA

Electrical data

Nominal wattage	8.5 W
Construction wattage	8.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	40 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor λ	> 0.70

Photometrical data

Luminous flux	1055 lm
Luminous efficacy	124 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	102.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	30.00 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Lifespan

Number of switching cycles	100000	
Additional product data		
Base (standard designation)	B22d	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the comproduction process for light-emitting diodes, the typical values she for the technical LED parameters are purely statistical values that not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Capabilities		
Dimmable	Yes	
Country-specific categorizations		
Order reference	LPCLADIM8,5W/86	
Energy labelling regulation data acc EU 2019/2015		
Light source cap-type (or other electric interface)	B22d	
Length	102.00 mm	
Height	60.00 mm	

LOGISTICAL DATA

Width

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075307261	Folding box	64 mm x 64 mm x 131 mm	42.00 g	0.54 dm ³
4058075307278	Shipping box 10	332 mm x 138 mm x 147 mm	574.00 g	6.73 dm ³

60.00 mm

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.