

PRODUCT DATASHEET ST GX53 40 100 ° 6 W/2700 K GX53

LED STAR GX53 | Flat LED Lamp with GX53 socket



Areas of application

- Area lighting
- As a downlight for marking walkways, doors, stairs, etc.
- Background lighting
- Domestic applications
- Entrance lighting
- Exhibitions, department stores
- For indoor use only
- Kitchen lighting
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Compact dimensions
- Easy installation
- Excellent luminous efficiency
- Good quality of light
- Low weight and low profile
- Three year guarantee
- Lower energy consumption than incandescent or halogen lamps

Product features

- 230 V line voltage operation
- High color consistency: ≤ 6 SDCM
- Not dimmable



- Type of protection: IP20
- Very long average lifetime 15,000 h (15 years at 2.7 h per day)

TECHNICAL DATA

Electrical data

Nominal wattage	6 W
Construction wattage	6.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	50 mA
Type of current	AC
Inrush current	3 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	45
Max. lamp number on MCB B16 A	75
Power factor λ	> 0.50

Photometrical data

Luminous intensity	145 cd
Luminous flux	470 lm
Nominal useful luminous flux 90°	470 lm
Luminous efficacy	78 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	145 cd
Rated LLMF at 6,000 h	0.80

Light technical data

Beam angle	100 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	31.00 mm

Diameter	75,0 mm
Maximum diameter	75 mm
Product weight	55.00 g
emperatures & operating conditions	
Ambient temperature range -20+40 °C	
Maximum temperature at tc test point	75 °C
Lifespan	
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	GX53
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	A+ 1)
Energy consumption	6.00 kWh/1000h
Type of protection	IP20
Standards	CE / CB / EAC
	RG0

LSGX5340100 6W/

Energy labelling regulation data acc EU 2019/2015

Order reference

Light source cap-type (or other electric interface)	GX53
Length	31.00 mm
Height	75,0 mm
Width	75,0 mm

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075052864	Blister 1	37 mm x 140 mm x 120 mm	67.00 g	0.62 dm ³
4058075052871	Shipping box 9	345 mm x 153 mm x 136 mm	785.00 g	7.18 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.osram-lamps.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.