

PRODUCT DATASHEET LED Base PIN 10 320° 0.9W 827 Clear G4

LED BASE PIN G4 12 V | Special LED lamps



Areas of application

- Atmospheric accent lighting throughout the home
- Shops, hotels and restaurants
- Foyers, offices
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Ideal for decorative and free-burning applications

Product features

- LED alternative to conventional low voltage lamps
- Mercury-free lamps





TECHNICAL DATA


Electrical data

Nominal wattage	0.9 W
Construction wattage	0.90 W
Nominal voltage	12 V
Operating mode	12V AC/DC ¹⁾
Claimed equiv. conventional lamp power	10 W
Nominal current	130 mA
Type of current	AC/DC
Inrush current	3.9 A
Max. lamp number on MCB B10 A	7
Max. lamp number on MCB B16 A	12
Total harmonic distortion	95 %
Power factor λ	> 0.50

¹⁾ Check ECG compatibility at ledvance.com/compatibility

Photometrical data

Luminous flux	100 lm
Luminous efficacy	111 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



349927_2700K_Evl_5630.eps

Light technical data

Beam angle	320 °
Warm-up time (60 %)	←0.50 s
Starting time	< 0.5 s

Dimensions & Weight

Overall length	33.00 mm
Diameter	12.00 mm
Maximum diameter	12 mm
Product weight	2.5 g

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	79.5 °C

Lifespan

Lifespan L70/B50 at 25 °C	10000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93

Additional product data

Base (standard designation)	G4
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear

Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	F 1)
Energy consumption	1.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG1
Country-specific categorizations Order reference	LEDBASEPIN10 CL
Country-specific categorizations Order reference	LEDBASEPIN10 CL
Order reference LOGISTICAL DATA	
Order reference LOGISTICAL DATA Temperature range at storage	LEDBASEPIN10 CL -20+80 °C
Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015	-20+80 °C
Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used	-20+80 °C
Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional	-20+80 °C LED NDLS
Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains	-20+80 °C LED NDLS NMLS
Order reference COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface)	-20+80 °C LED NDLS NMLS G4
Order reference COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	-20+80 °C LED NDLS NMLS G4 No
Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source	-20+80 °C LED NDLS NMLS G4 No No
Order reference COGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope	-20+80 °C LED NDLS NMLS G4 No No No
Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source	-20+80 °C LED NDLS NMLS G4 No No No No
Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source Anti-glare shield	-20+80 °C LED NDLS NMLS G4 No No No No No No
Order reference OGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source	-20+80 °C LED NDLS NMLS G4 No No No No

33.00 mm

12.00 mm

Length

Height

Width	12.00 mm
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
Displacement factor	>0.5
LED light source replaces a fluorescent light source	No
EPREL ID	522866,2365067
Model number	AC32120,AC32120,AC84117

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	LED PIN 20 NON-DIM 12V	
PDF	Declarations of conformity	LED lamp	
PDF	Declarations of conformity UKCA	LED lamp	
	Photometric and lighting design files	Document name	
	Spectral power distribution	349927_2700K_EvI_5630.eps	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075758001	Folding box 5	49 mm x 49 mm x 62 mm	27.50 g	0.15 dm ³
4058075758018	Shipping box 50	266 mm x 109 mm x 70 mm	260.00 g	2.03 dm ³
4058075786233	Shipping box 400	452 mm x 282 mm x 167 mm	3258.00 g	21.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.