

PRODUCT DATASHEET LED PIN 60 320° 4.9W 827 Clear G9

LED PIN G9 | LED lamps with retrofit pin base G9



Areas of application

- Atmospheric accent lighting throughout the home
- Shops, hotels and restaurants
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Good all-around light emission
- Long lifetime of up to 15,000 h
- Ideal for decorative and free-burning applications
- Three year guarantee
- Lower energy consumption than incandescent or halogen lamps

Product features

- LED alternative to conventional high voltage lamps
- Good quality of light; color rendering index $R_{a}\!\!:$ \geq 80; constant chromaticity





TECHNICAL DATA

Electrical data

Nominal wattage	4.9 W
Construction wattage	4.90 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	60 W
Nominal current	40 mA
Type of current	AC
Inrush current	7.1 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	84
Max. lamp number on MCB B16 A	105
Total harmonic distortion	133 %
Power factor λ	> 0.40

Photometrical data

Luminous flux	806 lm
Luminous efficacy	164 lm/W
Lumen main.fact.at end of nom.life time	0.93
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	80
Light color	827
Standard deviation of color matching	≤6 sdcm
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4




349927_2700K_Evl_5630.eps

Light technical data

Beam angle	320 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	59.00 mm
Diameter	18.00 mm
Maximum diameter	18 mm
Product weight	11.00 g

Temperatures & operating conditions

Ambient temperature range -20+40 °C	
Maximum temperature at tc test point	94.7 °C
ifespan	
Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.93
Additional product data	
Base (standard designation)	G9
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Clear
All technical parameters apply to the entire lamp / Due to production process for light-emitting diodes, the typical valued to the technical LED parameters are purely statistical valued not necessarily match the actual technical parameters of individual product, which can vary from the typical value	
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	C 1)
Energy consumption	5.00 kWh/1000h
Energy consumption Type of protection	5.00 kWh/1000h IP20
Type of protection	IP20
Type of protection Standards Photobiological safety group acc. to EN62778) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G	IP20 CE / EAC / UKCA RG1
Type of protection Standards Photobiological safety group acc. to EN62778) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G	IP20 CE / EAC / UKCA RG1
Type of protection Standards Photobiological safety group acc. to EN62778) Energy efficiency class (EEC) on a scale of A (highest efficiency) to Gountry-specific categorizations Order reference	IP20 CE / EAC / UKCA RG1 (lowest efficiency)
Type of protection Standards Photobiological safety group acc. to EN62778) Energy efficiency class (EEC) on a scale of A (highest efficiency) to Gountry-specific categorizations Order reference	IP20 CE / EAC / UKCA RG1 (lowest efficiency)
Type of protection Standards Photobiological safety group acc. to EN62778) Energy efficiency class (EEC) on a scale of A (highest efficiency) to Gountry-specific categorizations Order reference COGISTICAL DATA Temperature range at storage	IP20 CE / EAC / UKCA RG1 (lowest efficiency)
Type of protection Standards Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G. Country-specific categorizations Order reference LOGISTICAL DATA	IP20 CE / EAC / UKCA RG1 (lowest efficiency)

NDLS

Non-directional or directional

Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G9
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0 W
Claim of equivalent power	Yes
Length	59.00 mm
Height	18.00 mm
Width	18.00 mm
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.5
LED light source replaces a fluorescent light source	No
EPREL ID	2005319,2365051
Model number	AC64391,AC64391,AC84153

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	Declarations of conformity	LED PIN 60
PDF	Declarations of conformity	LED lamp
PDF	Declarations of conformity UKCA	LED PIN60

	Documents and certificates	Document name
PDF	Declarations of conformity UKCA	LED lamp

Photometric and lighting design files	Document name
Spectral power distribution	349927_2700K_EvI_5630.eps

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075840522	Folding box 1	20 mm x 49 mm x 95 mm	18.00 g	0.09 dm ³
4058075840539	Shipping box 6	109 mm x 79 mm x 104 mm	139.00 g	0.90 dm ³
4099854329159	Shipping box 48	236 mm x 176 mm x 237 mm	1442.00 g	9.84 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For dimming conformity see www.ledvance.com/dim
- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.