

PRODUCT DATASHEET ST5HO54-AC 26 W/6500 K 1147.80 mm

SubstiTUBE T5 ECO | LED tubes for operation with alternating current at 230 V line voltage



Areas of application

- Supermarkets and department stores
- Industry
- Public buildings, reception areas, offices, corridors, etc.
- General illumination within ambient temperatures from -20...+45 °C
- For indoor use only

Product benefits

- No bending thanks to glass technology
- Also suitable for operation at low temperatures
- Quick, simple and safe replacement

Product features

- Mercury-free and RoHS compliant
- Type of protection: IP20
- Professional LED lamps for line voltage



TECHNICAL DATA

Electrical data

Nominal wattage	26 W
Nominal voltage	220240 V
Nominal current	110 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.90

Photometrical data

Luminous flux	2860 lm
Nominal useful luminous flux 90°	2860 lm
Luminous efficacy	110 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	> 80
Light color	865
Standard deviation of color matching	≤6 sdcm

Light technical data

Beam angle	> 160.00 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	1147.80 mm
Diameter	17.80 mm
Product weight	121.94 g

Temperatures & operating conditions

Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70

Additional product data

Base (standard designation)	G5
Mercury content	0.0 mg

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Type of protection		IP20
Standards		ROHS / EMC
Photobiological safety group acc. to EN62778		RG0

Country-specific categorizations

Order reference	ST554E-1.2M26W/

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G5
Length	1147.80 mm
Height	17.80 mm
Width	17.80 mm

DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	ST554E-1.2M26W 865 230V ACHO G5 OSRAM
Light distribution curve type polar	ST554E-1.2M26W 865 230V ACHO G5 OSRAM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075757349	Sleeve 1	1,170 mm x 19 mm x 19 mm	137.00 g	0.42 dm ³
4058075757356	Shipping box 25	1,225 mm x 155 mm x 155 mm	4524.00 g	29.43 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.