

# PRODUCT DATASHEET ST8S-EM 8 W/6500 K 600 mm

LED STAR+ MOTION SENSOR T8 | LED tube with integrated motion sensor



#### Areas of application

- Corridors, stairways, parking garages
- Warehouses

#### Product benefits

- Integrated motion sensor with motion dependend dimming function
- Short payback period thanks to low energy consumption and maintenance costs
- $-\,$  Energy savings of up to 70 % compared to conventional T8 fluorescent lamp
- No bending thanks to glass technology
- Two year guarantee
- Instant flickerfree starting

#### Product features

- LED alternative to classic T8 fluorescent lamps in CCG luminaires
- Luminous efficacy: up to 100 lm/W
- Two step dimming: 30 % and 100 % light output
- Lifetime up to 30,000 h



- High color consistency:  $\leq$  6 SDCM
- Color rendering index  $R_a$ :  $\geq 80$
- Bright, robust and durable
- Uniform illumination

# TECHNICAL DATA

# Electrical data

Nominal wattage	8 W
Construction wattage	8.00 W
Nominal voltage	220240 V
Nominal current	40 mA
Type of current	AC
Power factor λ	0.90

# Photometrical data

Luminous flux	900 lm
Luminous efficacy	112 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcm

# Light technical data

Beam angle	200 °
Warm-up time (60 %)	< 1.00 s
Starting time	< 1.0 s

# Dimensions & Weight

Overall length	603.00 mm
Diameter	28.00 mm
Product weight	140.00 g

# Temperatures & operating conditions

Ambient temperature range -10+45 °C
-------------------------------------

# Lifespan

Number of switching cycles	50000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	0.90

### Additional product data

Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes

### Capabilities

Dimmable	Yes
<del></del>	

#### Certificates & Standards

Energy efficiency class	A+ <sup>1)</sup>
Energy consumption	8.80 kWh/1000h
Type of protection	IP20

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

### Country-specific categorizations

### LOGISTICAL DATA

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	603.00 mm
Height	28.00 mm
Width	28.00 mm

#### **EQUIPMENT / ACCESSORIES**

- Suitable for operation on conventional control gear

### Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

# DOWNLOAD DATA

Photometric and lighting design files	Document name
IES file (IES)	ST8S Motion sensor tube 8W/865 800lm
LDT file (Eulumdat)	ST8S Motion sensor tube 8W/865 800lm

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075055599	Sleeve 1	690 mm x 31 mm x 31 mm	0.19 g	0.66 dm <sup>3</sup>
4058075055605	Shipping box 25	750 mm x 225 mm x 235 mm	5529.00 g	39.66 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.