

## PRODUCT DATASHEET

### ST8S-EM 20 W/6500 K 1500 mm

LED STAR+ MOTION SENSOR T8 | LED tube with integrated motion sensor



#### Areas of application

- Corridors, stairways, parking garages
- Warehouses

#### Product benefits

- Integrated motion sensor with motion dependend dimming function
- Short payback period thanks to low energy consumption and maintenance costs
- Energy savings of up to 70 % compared to conventional T8 fluorescent lamp
- No bending thanks to glass technology
- Two year guarantee
- Instant flickerfree starting

#### Product features

- LED alternative to classic T8 fluorescent lamps in CCG luminaires
- Luminous efficacy: up to 100 lm/W
- Two step dimming: 30 % and 100 % light output
- Lifetime up to 30,000 h



- High color consistency:  $\leq 6$  SDCM
- Color rendering index  $R_a: \geq 80$
- Bright, robust and durable
- Uniform illumination

## TECHNICAL DATA

### Electrical data

Nominal wattage	20 W
Construction wattage	20.00 W
Nominal voltage	220...240 V
Nominal current	92 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	0.90

### Photometrical data

Luminous flux	2400 lm
Luminous efficacy	120 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	83
Light color	865
Standard deviation of color matching	$\leq 5$ sdc <sub>m</sub>

### Light technical data

Beam angle	> 190 °
Starting time	< 0.5 s

### Dimensions & Weight

Overall length	1513.00 mm
Diameter	25.30 mm
Product weight	270.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
---------------------------	--------------

### Lifespan

Number of switching cycles	200000
----------------------------	--------

### Additional product data

Base (standard designation)	G13
-----------------------------	-----

Mercury content	0.0 mg
-----------------	--------

### Capabilities

Dimmable	No
----------	----

### Certificates & Standards

Type of protection	IP20
Photobiological safety group acc. to EN62778	RG0

### Country-specific categorizations

Order reference	ST8S-1.5M 20W/8
-----------------	-----------------

### LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	1513.00 mm
Height	25.30 mm
Width	25.30 mm



### EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear

### Safety advice

- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

### DOWNLOAD DATA

Photometric and lighting design files		Document name
	IES file (IES)	ST8S-1.5M 20W 865 EM
	Light distribution curve type polar	ST8S-1.5M 20W 865 EM

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075660816	Sleeve 1	1,605 mm x 29 mm x 29 mm	304.00 g	1.35 dm <sup>3</sup>
4058075660823	Shipping box 10	1,652 mm x 210 mm x 115 mm	3882.00 g	39.90 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### Legal advice

– When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.