

# PRODUCT DATASHEET DECOSTAR 51 PRO 20 W 12 V 10° GU5.3

DECOSTAR® 51 PRO | Halogen dichroic reflector lamps with 51 mm diameter



#### Areas of application

- General illumination
- Kitchen lighting
- Dining table lighting
- Mirror lighting
- Workplace lighting
- Shops
- Restaurants, hotels and similar prestigious applications

## **Product benefits**

- Brilliant accent lighting
- Significantly lower CO<sub>2</sub> emissions compared to standard version
- Constant luminous intensity and constant color location throughout the lifetime
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

## Product features

- Average life: 5,000 h
- 100 % dimmable
- Color rendering index Ra: 100



- Color temperature: 3,000 K
- Diameter: 51 mm
- Deco cover
- IRC technology


# TECHNICAL DATA

# Electrical data

Nominal wattage	20 W
Construction wattage	20.00 W
Nominal voltage	12 V
Claimed equiv. conventional lamp power	35 W
Power factor $\lambda$	1.00

#### Photometrical data

Luminous intensity	5500 cd
Luminous flux	380 lm
Nominal useful luminous flux 90°	300 lm
Luminous efficacy	19 lm/W
Lumen main.fact.at end of nom.life time	0.75
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
Rated peak intensity	5500 cd
UV protection	Yes



349622\_HAL\_DICRO\_AK\_IRC

# Light technical data

Beam angle	10 °
Warm-up time (60 %)	0.00 s
Starting time	0.0 s

# Dimensions & Weight

Overall length	45.00 mm
Diameter	50.7 mm
Maximum diameter	51 mm
Product weight	31.65 g
Lifespan	
Number of switching cycles	125000
Additional product data	
Base (standard designation)	GU5.3
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Reflector
Capabilities	
Dimmable	Yes
Burning position	Any
Certificates & Standards	
Energy efficiency class	G
Energy consumption	22.00 kWh/1000h
Country-specific categorizations	
ILCOS	HRGS//UBIB-20-12-GU5.3-51/10
Order reference	48860 ECO SP
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	OTHER
Non-directional or directional	DLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GU5.3
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Length	46.00 mm

Height	50.7 mm
Width	50.7 mm
Chromaticity coordinate x	0.437
Chromaticity coordinate y	0.404
Beam angle correspondence	NARROW_CONE_90
EPREL ID	1337630
Model number	A33015F

## DOWNLOAD DATA

Photometric and lighting design files	Document name	
Spectral power distribution	349622_HAL_DICRO_AK_IRC	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300620169	Folding box 1	58 mm x 46 mm x 46 mm	38.00 g	0.12 dm <sup>3</sup>
4050300620176	Shipping box 20	238 mm x 122 mm x 123 mm	836.00 g	3.57 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.