

PRODUCT DATASHEET DECOSTAR 51 TITAN 35 W 12 V 24° GU5.3

DECOSTAR® 51 TITAN | Halogen dichroic reflector lamps with 51 mm diameter



Areas of application

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

Product benefits

- Brilliant accent light
- Constant bluish appearance of the light escaping at the back of the reflector
- Dichroic reflector reduces the heat in the light beam by up to 66 %
- Constant luminous intensity and constant color location throughout the lifetime
- Flat clear shield
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Contains no mercury

Product features

- Average life: 4,000 h
- 100 % dimmable



- Color rendering index Ra: 100
- Color temperature: 3,000 K
- Diameter: 51 mm
- Deco cover


TECHNICAL DATA

Electrical data

Nominal wattage	35 W
Construction wattage	35.00 W
Nominal voltage	12 V
Power factor λ	1.00

Photometrical data

Luminous intensity	3100 cd
Luminous flux	700 lm
Nominal useful luminous flux 90°	550 lm
Luminous efficacy	20 lm/W
Lumen main.fact.at end of nom.life time	0.75
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
Rated peak intensity	3100 cd
UV protection	Yes



349643_HAL_DICRO_AK

Light technical data

Beam angle	24 °
Warm-up time (60 %)	0.00 s
Starting time	0.0 s

Dimensions & Weight

Overall length	45.00 mm
----------------	----------

Diameter	50.7 mm
Maximum diameter	51 mm
Product weight	31.5 g
Lifespan	
Number of switching cycles 100000	
Additional product data	
Base (standard designation)	GU5.3
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Reflector
Capabilities	
Dimmable	Yes
Burning position	Any
Certificates & Standards	
Energy efficiency class	G
Energy consumption	38.00 kWh/1000h
Country-specific categorizations	
ILCOS	HRGS//UB-35-12-GU5.3-51/24
Order reference	46865 FL
Energy labelling regulation data acc EU 2019/2015	
Lighting technology used	OTHER
Non-directional or directional	DLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	GU5.3
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Length	46.00 mm
11.11	

50.7 mm

Height

Width	50.7 mm
Chromaticity coordinate x	0.437
Chromaticity coordinate y	0.404
Beam angle correspondence	NARROW_CONE_90
EPREL ID	1337700
Model number	A35040A

DOWNLOAD DATA

Photometric and lighting design files Document name	
Spectral power distribution	349643_HAL_DICRO_AK

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300476414	Folding box 1	58 mm x 46 mm x 46 mm	38.00 g	0.12 dm ³
4050300532028	Shipping box 20	238 mm x 123 mm x 123 mm	836.00 g	3.60 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.